



उत्पाद मन्थन
आई एस 4621:1975 के अनुसार
जनता में उपयोग के लिए संकेत बोल्ट स्नान और शौचालय के लिए
दस्तावेज संख्या – पीएम/आईएस 4621/1/फेब्रुअरी 2023

भारतीय मानक ब्यूरो की स्कीम-I (अनुरूपता मूल्यांकन) विनियम, 2018 के तहत यह उत्पाद मैन्युअल प्रमाणीकरण के प्रचालन में रीति और पारिश्रिता की सुसंगतता सुनिश्चित करने के लिए सभी क्षेत्रीय/शाखा कार्यालयों और लाइसेंसी द्वारा संदर्भ सामग्री के रूप में उपयोग किया जाएगा। बीआईएस प्रमाणीकरण लाइसेंस/ प्रमाणपत्र प्राप्त करने के इच्छुक भावी आवेदकों द्वारा भी इस दस्तावेज का उपयोग किया जा सकता है।

PRODUCT MANUAL FOR
INDICATING BOLTS FOR USE IN PUBLIC BATHS AND LAVATORIES
ACCORDING to IS 4621:1975

Document No.-PM/IS 4621/1/ Feb 2023

This Product Manual shall be used as reference material by all Regional/Branch Offices & licensees to ensure coherence of practice and transparency in operation of certification under Scheme-I of Bureau of Indian Standards (Conformity Assessment) Regulations, 2018 for various products. The document may also be used by prospective applicants desirous of obtaining BIS certification licence/certificate.

भारतीय मानक ब्यूरो
 BUREAU OF INDIAN STANDARDS
 मानक भवन, ९, बहादुर शाह ज़फ़र मार्ग
 Manak Bhawan, 9, Bahadur Shah Zafar Marg
 नई ददल्ली- ११०००२
 New Delhi – 110002



PRODUCT MANUAL FOR INDICATING BOLTS FOR USE IN PUBLIC BATHS AND LAVATORIES ACCORDING TO IS 4621: 1975

This Product Manual shall be used as reference material by all Regional/Branch Offices & licensees to ensure coherence of practice and transparency in operation of certification under Scheme-I of Bureau of Indian Standards (Conformity Assessment) Regulations, 2018 for various products. The document may also be used by prospective applicants desirous of obtaining BIS certification licence/certificate.

1.	Product	:	IS 4621: 1975
	Title	:	Indicating Bolts For Use In Public Baths and Lavatories
	No. of Amendments	:	Nil
2.	Sampling Guidelines:		
a)	Raw material	:	Aluminum alloy casting for body, knob, indicating spindle and Gears- as per IS 617 Extruded aluminum alloy for body, knob and indicating spindle- as per IS 733 Brass casting for body, knob, indicating spindle, Indicating disc and Gears- as per IS 292 Extruded brass for body, knob and indicating spindle- as per IS 319 Zinc alloy base die casting for body, knob and indicating spindle- as per IS 742 Aluminum alloy sheet for indicating disc- as per IS 737 Note: Manufacturers should check for the latest applicable cross referred Indian Standards on raw material and test methods with BIS
b)	Grouping guidelines	:	Please refer ANNEX –A
c)	Sample Size	:	6 Nos.
3.	List of Test Equipment	:	Please refer ANNEX –B
4.	Scheme of Inspection and Testing	:	Please refer ANNEX –C
5.	Possible tests in a day	:	All tests
6.	Scope of the Licence:	:	Licence is granted to use Standard Mark as per IS 4621:1975 with the following scope:
	Name of product	:	Indicating Bolts for use in Public Baths and Lavatories
	Type of operation	:	Gear Work/Displacement
	Size	:	Size 1/Size 2

BUREAU OF INDIAN STANDARDS
Manak Bhawan, 9, Bahadur Shah Zafar Marg,
New Delhi – 110002

ANNEX A**Grouping Guidelines**

1. Flush Bolts as per IS 4621: 1975 are classified in to different varieties based on the following:
 - **Material of Body:** Cast Brass/ Cast Aluminum Alloy/ Extruded Aluminum Alloy/Extruded Brass/Zinc base alloy
 - **Type of operations:** Gear Work , Displacement
 - **Sizes:** Size 1/ Size 2
2. Considering the above, sample of indicating Bolt of each material, type of operation and size shall be tested to cover both types and sizes.
3. The Firm shall declare the varieties of Indicating Bolts they intend to cover in the Licence. The Scope of Licence may be restricted based on the Manufacturing and testing capabilities of the Manufacturer.
4. During the operation of the Licence, BO shall ensure that all the types and sizes covered in the Licence are tested in rotation, to the extent possible.

ANNEX B**List of Test Equipment***Major test equipment required to test as per the Indian Standard*

S.no.	Tests used in with Clause Reference		Test Equipment
	Cl. No.	Test	
1.	4.1, Fig.1, Table 1	Dimensions	Vernier caliper, Micrometer
2.	7	Tests for anodizing on Aluminum Bolts	Chemicals with reagents or Eddy current tester or other test equipment as per IS 1868 for coating thickness, Salt spray chamber for corrosion resistance test, other apparatus for abrasion resistance, resistance to crazing, fastness to light, Light reflection as per IS 5523, Apparatus for Electric potential breakdown (as per IS 6910) and continuity tests (as per IS 8375)

The above list is indicative only and may not be treated as exhaustive

ANNEX C**Scheme of Inspection and Testing**

1. LABORATORY - A laboratory shall be maintained which shall be suitably equipped (as per the requirement given in column 2 of Table 1) and staffed, where different tests given in the specification shall be carried out in accordance with the methods given in the specification.

1.1 The manufacturer shall prepare a calibration plan for the test equipments.

2. TEST RECORDS – The manufacturer shall maintain test records for the tests carried out to establish conformity.

3. LABELLING AND MARKING – As per the requirements of IS 4621: 1975. Additionally, type of operation and Size shall also be marked on each piece or package.

4. CONTROL UNIT- All Indicating Bolts of same material of components, Type of operation and Size, manufactured under similar conditions from same consignment of raw material in a day shall constitute a control unit.

5. LEVELS OF CONTROL - The tests as indicated in column 1 of Table 1 and the levels of control in column 3 of Table 1, shall be carried out on the whole production of the factory which is covered by this plan and appropriate records maintained in accordance with paragraph 2 above.

5.1 All the production which conforms to the Indian Standards and covered by the licence should be marked with Standard Mark.

5.2 Manufacturers should check for the latest applicable cross referred Indian Standards on raw material and test methods with BIS.

6. REJECTIONS – Disposal of non-conforming product shall be done in such a way so as to ensure that there is no violation of provisions of BIS Act, 2016.

TABLE 1

(1)				(2)	(3)		
Test Details				Test equipment requirement R: required (or) S: Sub-contracting permitted	Levels of Control		
Cl.	Requirement	Test Method			No. of Sample	Frequency	Remarks
		Clause	Reference				
5.1	Raw Material	5.1, Table 2	IS 4621 IS 617, IS 733, IS 319, IS 742, IS 737, IS 292	S	One	Each Consignment	No further testing is required if material is received with test certificate or is ISI Marked.
4.1	Dimensions	4.1, Table 1, Fig.1	IS 4621	R	Firm to have adequate in-process controls to check compliance of this parameter as per the tolerances given in the Indian Standard. However, appropriate records shall be maintained by the manufacturer for evidence of conformity		
6.1	Manufacture	6.1	IS 4621	R			
7.1	Workmanship and Finish	7.1	IS 4621	R			
7.1	Anodizing test for Aluminum Body Indicating Bolts						
	Thickness	7.1 9	IS 4621 IS 1868	R	One	Once in 3 months for each variety manufactured	
	Quality of sealing	7.1 10	IS 4621 IS 1868	S	One	Once in 3 months for each variety manufactured	
	Colour and appearance	7.1 11	IS 4621 IS 1868	R	One	Once in 3 months for each variety manufactured	
	Corrosion resistance	7.1 12	IS 4621 IS 1868	R	One	Once in 3 months for each variety manufactured	

	Abrasion resistance, If required by purchaser	7.1 13	IS 4621 IS 1868	R	As per the requirement of purchaser		
	Resistance to crazing by deformation	7.1 14	IS 4621 IS 1868	R	One	Once in 3 months for each variety manufactured	
	Fastness to light	7.1 15	IS 4621 IS 1868	S	One	Once in 3 months for each variety manufactured	
	Light reflection properties	7.1 16	IS 4621 IS 1868	S	One	Once in 3 months for each variety manufactured	
	Electrical Breakdown potential, if required by purchaser	7.1 17	IS 4621 IS 1868	S	As per the requirement of purchaser		

Note-1: Sub-contracting is permitted to a laboratory recognized by the Bureau or Government laboratories empanelled by the Bureau.

Note-2: Levels of control given in column 3 are only recommendatory in nature. The manufacturer may define the control unit/batch/lot and submit his own levels of control in column 3 with proper justification for approval by BO Head.