



उत्पाद मैनुअल
जिप्सम प्लास्टर बोर्ड - भाग 3 प्रबलित जिप्सम के प्लास्टर
बोर्ड और छत की टाइले,
आई एस 2095 (भाग 3):2022 के अनुसार

PRODUCT MANUAL FOR
GYPSUM PLASTER BOARDS: PART 3 - REINFORCED GYPSUM
PLASTER BOARDS AND CEILING TILES
ACCORDING TO IS 2095 (PART 3):2022

विभिन्न उत्पादों के लिए भारतीय मानक ब्यूरो) अनुरूपता मूल्यांकन (विनियम, 2018 की योजना -I के तहत प्रमाणन के संचालन में एकरूपता और पारदर्शिता के लिए इस उत्पाद मैनुअल का उपयोग सभी क्षेत्रीय / शाखा कार्यालयों और लाइसेंसधारियों द्वारा संदर्भ सामग्री के रूप में किया जाएगा। दस्तावेज़ का उपयोग बीआईएस प्रमाणन प्राप्त करने के इच्छुक संभावित आवेदकों द्वारा भी किया जा सकता है।

This Product Manual shall be used as reference material by all Regional/Branch Offices & licensees to ensure uniformity of practice and transparency in operation of certification under Scheme-I of Bureau of Indian Standards (Conformity Assessment) Regulations, 2018 for various products. The document may also be used by prospective applicants desirous of obtaining BIS certification.

1.	मानक संख्या IS No.	:	IS 2095 (PART 3) : 2022
	शीर्षक Title	:	Product Manual For Gypsum Plaster Boards: Part 3 - Reinforced Gypsum Plaster Boards And Ceiling Tiles
	संशोधनों की संख्या No. of amendments	:	1
2.	नमूना दिशानिर्देश Sampling Guidelines		
a)	कच्चा माल Raw material	:	(i) Gypsum (natural gypsum or by-product gypsum) used for the manufacture of gypsum plaster board shall comply with the requirements given in Table 1 of IS 2095 (Pt 3):2022. (ii) Fibre shall conform to Clause 4.2 of IS 2095 (Pt 3):2022. Note: This section indicates the requirements for raw material (if specified in the IS) for which compliance is to be established during Grant of Licence/Change in Scope of Licence/ Factory Surveillance
b)	समूहीकरण दिशानिर्देश Grouping Guidelines	:	Please refer to Annex-A
c)	नमूने का परिमाण Sample Quantity	:	4 Boards of full size Note: This section indicates the quantity of the sample of the product and/or

		the raw material (if applicable), required to be sent to the laboratory for testing, for the purpose of Grant of Licence/Change in Scope of Licence/ Factory Surveillance (incase of market surveillance, effort may be made to procure therequired quantity of product sample, as far as possible since raw material sample may not be available in market)
3.	परीक्षण उपकरणों की सूची List of Test Equipment	: Please refer to Annex-B
4.	निरीक्षण और परीक्षण की स्कीम Scheme of Inspection and Testing	: Please refer to Annex-C
5.	एक दिन में संभावित परीक्षण Possible tests in a day	
	(i)Dimensions (Clause 6.1), (ii) Finish (Clause 6.8) Note: This section is for the guidance of BIS Certification Officers/Technical Auditors of BIS Authorized Outside Surveillance Agencies (OSAs) during factory inspection to provide readyreference regarding the tests which can be witnessed during the inspection in the factory by the officer/auditor.	
6.	लाइसेंस का दायरा /Scope of the Licence:	
	“Licence is granted to use Standard Mark as per IS 2095 (PART 3) : 2022 with the following scope:	
	Name of the product	Reinforced Gypsum Plaster Boards And Ceiling Tiles
	Size (mm)	
	Type	Board/ Tiles
	Reinforcement	Fibre/ Gypsum

भारतीय मानक ब्यूरो
 BUREAU OF INDIAN STANDARDS
 मानक भवन, ९, बहादुर शाह ज़फ़र मार्ग
 Manak Bhawan, 9, Bahadur Shah Zafar Marg
 नई दिल्ली- ११०००२
 New Delhi – 110002

ANNEX-A

Grouping Guidelines

1. Reinforced gypsum plaster boards covered in IS 2095 (PART 3) are classified as under:
 - a) Types : Board/ Tiles
 - b) Reinforcement: Fibre/ Glass
 - c) Dimensions : Length x Width x Thickness
(Note : Gypsum plaster units with other dimension may be manufactured subject to mutual agreement between the purchaser and the manufacturer, however the same tolerance shall be applicable.)
2. Value of Impact Strength differs for different thicknesses of boards and tiles.
3. Considering the above, following grouping guidelines for GoL/ CSoL have been developed:
 - (a) Each type, thickness and reinforcement shall be tested for all requirements to cover that particular type, thickness and reinforcement in the scope of licence.
 - (b) Board of highest width and highest length shall be tested for all requirements to cover boards of all widths and lengths upto and including the width & length tested.
4. The Scope of Licence may be restricted based on the Manufacturing and Testing capabilities of the Manufacturer.
5. During the operation of the Licence, BO shall ensure that all varieties covered in the Licence may be tested in rotation, to the extent possible.

ANNEX-B

List of Test Equipment

(INDICATIVE LIST, FOR GUIDANCE ONLY)

Sl. No.	Tests used in with Clause Reference	Test Equipment
1.	Dimensions(Clause 6.1)	-Measuring tape -Steel scale -Micro meter -Straightness edge -Squareness edge
2	Density (Clause 6.3)	-Metal rule -Micrometer/dial gauge/caliper with anvil diameter -Weighing balance -Cutter -Drying oven
3	Flexural Breaking Load (Clause 6.4)	-Weighing balance -Measuring tape, cutter -Conditioning chamber - Test equipment as per fig 1 of IS 2542 (Part 2/ Sec 4)
4	Impact Strength (Clause 6.5)	-Sample cutter -Vernier caliper -Charpy Impact tester
5	Water Absorption (Clause 6.6)	-Weighing balance -Water bath - Cutter -Conditioning chamber -Stop watch
6	Jolting Test (Clause 6.7)	-Cutter -Measuring tape -Horizontal table

ANNEX C

SCHEME OF INSPECTION AND TESTING

1. QUALITY ASSURANCE PLAN

1.1 It is expected that manufacturers (licensees/applicants) will implement a Quality Assurance Plan i.e. a plan of regular testing and in-process controls, designed to ensure that the product bearing the Standard Mark conforms to all requirements of the Indian Standard.

1.2 The manufacturers shall define a Quality Assurance Plan defining the control unit (i.e. lot/batch etc.) and the levels of control (i.e. the frequency and number of samples for conducting the different tests as per the Indian Standard) and submit the same to BIS Branch Office for information. The manufacturer shall comply with the same and maintain test records in accordance with para 2.4.

1.3 RECOMMENDED LEVELS OF CONTROL/CONTROL UNIT:

1. 1.3.1 For the guidance of manufacturers, the recommended definition of control unit All gypsum boards of same type, size and reinforcement produced in a day from similar raw material under similar condition of production in a day shall constitute a control unit.

1.3.2 For the guidance of manufacturers in preparing the Quality Assurance Plan, recommended levels of control are given in **Table 1**.

1.3.3 The manufacturer shall ensure inspection and testing as per the Quality Assurance Plan submitted by them on the whole production of the factory which is covered by this plan. Alternatively, the manufacturer has the option of adherence to the quality plan as per levels of control recommended in column 3 of Table 1.

1.4 However, all manufacturers shall ensure compliance of their products to all the requirements of the Indian Standard.

2 ENSURING COMPLIANCE THROUGH TESTING- It is expected that manufacturers (licensees/applicants) will establish a suitably equipped and staffed in house laboratory (In house testing facility) for testing at least those parameters of the Indian Standard which require routine testing for ensuring quality of the product. This includes in-process controls as may be defined and put in place by the manufacturer and testing parameters/requirements which can only be performed in the factory.

2.3 For the guidance of manufacturers, Table 1 giving the recommended levels of control is given below. Column 2 of Table 1 indicates routine tests where test equipment is required in house as “R” or other tests which can be subcontracted as “S”. Subcontracting is permitted to BIS recognized/empanelled laboratory or any other laboratory having valid NABL accreditation as per IS/ISO/IEC 17025.

2.4 For MSME manufacturers, the requirement of maintaining a laboratory/in-house testing facility for routine tests (indicated as “R” in Column 2 of Table 1) is also optional.

2.4.2 MSME manufacturers may utilize common cluster based facilities as per guidelines for the utilization of cluster based test facilities by MSMEs or the provisions of Sharing of testing facilities or get testing done from

BIS recognized/empaneled laboratory or any other laboratory having valid NABL accreditation as per IS/ISO/IEC 17025.

2.5 Large Scale manufacturers shall maintain an in-house laboratory equipped at least with test facilities for routine tests (indicated as “R” in Column 2 of Table 1), where different tests given in the specification shall be carried out in accordance with the method given in the specification. They shall also implement a calibration plan for the in-house test equipment.

2.5.2 Alternatively, in lieu of an in-house laboratory, large scale manufacturers can also utilize the provisions of Sharing of testing facilities as per the Guidelines for Grant of Licence available on BIS website www.bis.gov.in. (Under Conformity Assessment>Product Certification Process). Even for subcontracted tests, provisions for sharing of testing facilities can be utilized.

2.6 TEST RECORDS- The manufacturers maintaining an in-house laboratory or utilizing common cluster based facilities or shared test facilities shall maintain test records for the tests carried out to establish conformity. For the tests being subcontracted to BIS recognized/empaneled laboratory or any other laboratory having valid NABL accreditation as per IS/ISO/IEC 17025, test reports issued by the laboratories shall be available for inspection by BIS.

3 PACKING AND MARKING - The Standard Mark as given in the Schedule of the licence shall be legibly and indelibly marked on each gypsum board, provided always that the product so marked conforms to all requirements of the specification.

3.3 Marking shall be done as per the Indian Standard.

3.4 Additional Marking requirements: Each product/packing shall also be marked with the following additional requirement:

a) “For BIS certification details please visit www.bis.gov.in”

4 REJECTION - All the production which conforms to the Indian Standard and covered under the scope of this licence shall be marked with the Standard Mark. Disposal of non-conforming product shall be done in such a way so as to ensure that there is no violation of provisions of BIS Act, 2016.

TABLE 1
(ONLY FOR GUIDANCE PURPOSE)

(1)				(2)	(3)		
Test Details				Test equipment requirement R: required (or) S: Sub-contracting permitted	Levels of Control		
Cl.	Requirement	Clause Reference	Test Methods		No. of Sample	Frequency	Remarks
4.1	Gypsum plaster	4.1	IS 2095 (PART 3)	S	One	Each consignment	No further testing is required if ISI marked or accompanied with test certificate.
4.2	Fibre	4.2	IS 2095 (PART 3)				
5	Manufacture	5	IS 2095 (PART 3)	R	Firm to have adequate in-process controls to check compliance of this parameter as per the tolerances given in the Indian Standard. However, appropriate records shall be maintained by the manufacturer for evidence of conformity		
6.1	Dimension	6.1	IS 2095 (PART 3)	R			
6.3	Density	6.3	IS 2095 (PART 3)	R	One	Each Control unit	-
6.4	Flexural Breaking Load	6.4	IS 2095 (PART 3)	R	One	Each Control unit	-
6.5	Impact strength	6.5	IS 2095 (PART 3)	R	One	Each Control unit	-
6.6	Water absorption	6.6	IS 2095 (PART 3)	R	One	Each Control unit	-
6.7	Jolting Test	6.7	IS 2095 (PART 3)	R	One	Each Control unit	-
6.8	Finish	6.8	IS 2095 (PART 3)	R	Firm to have adequate in-process controls to check compliance of this parameter as per the tolerances given in the Indian Standard. However, appropriate records shall be maintained by the manufacturer for evidence of conformity		