



उत्पाद मैनुअल
शिशु आहार अनुसरित फार्मूला विशिष्टि
IS 15757 : 2022 के अनुसार

PRODUCT MANUAL FOR
INFANT FOOD - FOLLOW- UP FORMULA - SPECIFICATION
ACCORDING TO IS 15757: 2022

विभिन्न उत्पादों के लिए भारतीय मानक ब्यूरो) अनुरूपता मूल्यांकन (विनियम, 2018 की योजना -I के तहत प्रमाणन के संचालन में एकरूपता और पारदर्शिता के लिए इस उत्पाद मैनुअल का उपयोग सभी क्षेत्रीय / शाखा कार्यालयों और लाइसेंसधारियों द्वारा संदर्भ सामग्री के रूप में किया जाएगा। दस्तावेज़ का उपयोग बीआईएस प्रमाणन प्राप्त करने के इच्छुक संभावित आवेदकों द्वारा भी किया जा सकता है।

This Product Manual shall be used as reference material by all Regional/Branch Offices & licensees to ensure uniformity of practice and transparency in operation of certification under Scheme-I of Bureau of Indian Standards (Conformity Assessment) Regulations, 2018 for various products. The document may also be used by prospective applicants desirous of obtaining BIS certification.

1.	मानक संख्या IS No.	:	IS 15757: 2022
	शीर्षक Title	:	Infant Food - Follow- Up Formula
	संशोधनों की संख्या No. of amendments	:	02
2.	नमूना दिशानिर्देश Sampling Guidelines		
a)	कच्चा माल Raw material	:	a) Manufacturer to submit declaration/ undertaking in compliance to Clause 4.3.1, 4.3.3 and 4.4 of IS 15757:2022. b) Manufacturer to maintain test report/test certificates w.r.t. fat and linoleic acid in compliance to Clause 4.3.2 of IS 15757:2022. Manufacturer to submit declaration/ undertaking w.r.t. partially hydrogenated oils and fats in compliance to Clause 4.3.2 of IS 15757:2022 c) In case the manufacturer opts for addition of any Optional Ingredients as per provisions of Cl. 4.5 of IS 15757:2022, undertakings/declaration in compliance to clause 5.7 and/or 5.7.1 of IS 14433:2022 to be submitted. d) In case the manufacturer opts for addition of any Food Additives, it is required to submit declaration/ undertaking in compliance to Clause 4.6.1 and/or Clause 4.6.2 of IS

		15757:2022 In case of addition of pesticide residue, antibiotic and veterinary drug residues, naturally occurring toxins and other contaminants the manufacturer is required to submit declaration/undertaking in compliance to Clause 4.10 of IS 15757:2022 Note: This section indicates the requirements for raw material (if specified in the IS) for which compliance is to be established during Grant of Licence / Change in Scope of Licence/Factory Surveillance.
b)	समूहीकरण दिशानिर्देश Grouping Guidelines	: NA
c)	नमूने का परिमाण Sample Quantity	: 2 x 500gm Note: This section indicates the quantity of the sample of the product and/or the raw material (if applicable), required to be sent to the laboratory for testing, for the purpose of Grant of Licence/Change in Scope of Licence/ Factory Surveillance (incase of market surveillance, effort may be made to procure therequired quantity of product sample, as far as possible since raw material sample may not be available in market)
d)	परीक्षण अनुरोध में घोषित किए जाने वाले पैरामीटर Parameters to be Declared in Test Request	: Name of the product
3.	परीक्षण उपकरणों की सूची List of Test Equipment	: कृ पया Annex-ए देखें Please see Annex – A
4.	निरीक्षण और परीक्षण की स्कीम Scheme of Inspection and Testing	: कृ पया Annex-B देखें Please see Annex – B
5.	एक दिन में संभावित परीक्षण Possible tests in a day	
	i) Description ii) Scorched Particles iii) Moisture iv) Total Milk Protein v) Total Fat vi) Total ash vii) Acid insoluble ash in dilute hydrochloric acid viii) Solubility Index Note: This section is for the guidance of BIS Certification Officers/Technical Auditors of BIS Authorized Outside Surveillance Agencies (OSAs) during factory inspection to provide readyreference regarding the tests which can be witnessed during the inspection in the factory by the officer/auditor.	
6.	लाइसेंस का दायरा /Scope of the Licence:	
	Licence is granted to use Standard Mark as per 15757 : 2022 with the following scope:	
	Name of the product	Infant Food - Follow- Up Formula

ANNEX – A
List of test equipment

(INDICATIVE LIST, FOR GUIDANCE ONLY)

Sr. No.	Tests used in with Clause Reference	Test equipment/Chemical
1.	Scorched particles Cl. 4.2	Balance (approximately 500 g capacity and LC=0.1 g), Mixer, Scorched Particles Filtering Discs, Scorched Particles Discs Test Cards, Scorched Particles Tester, Diglycol laurate S or Antifoam B emulsion, distilled water
2.	Moisture Cl. 4.8, Table 1, Sl. No.(i)	Hot Air Oven, Electronic Balance, Desiccator
3.	Total milk protein Cl. 4.8, Table 1, Sl. No.(ii)	Potassium sulfate (K ₂ SO ₄) nitrogen free, Copper (II) sulfate pentahydrate solution, Sulfuric acid (H ₂ SO ₄), Sodium hydroxide (NaOH) solution, methyl red, ethanol, bromocresol green, Boric acid solution, Hydrochloric acid, Ammonium sulfate, Tryptophan or lysine hydrochloride, Water Bath, Analytical balance, Burette or automatic pipette, Graduated measuring cylinders, Digestion flasks (Kjeldahl), of 500 ml or 800 ml capacities, Boiling aids, e.g. hard pieces of porcelain or high-purity amphoteric alundum (i.e. carbarundum) granules, Digestion apparatus, Distillation apparatus, Digestion block and Digestion tubes, Exhaust manifold, Centrifugal scrubber apparatus or filter pump or aspirator, Distillation unit, Automatic titrator provided with a pH meter, Filter paper, Illuminated magnetic stirrer plate
4.	Total fat Cl. 4.8, Table 1, Sl.No.(iii)	Ammonia solution, containing a mass fraction of NH ₃ of approximately 25 %, Ethanol (C ₂ H ₅ OH), or ethanol denatured by methanol, containing a volume fraction of ethanol of at least 94%, Indicator solution (optional), Bromocresol purple solution, Patent blue V, Diethyl ether, free from peroxides, Light petroleum, with any boiling range between 30 °C and 60 °C, Analytical balance (capable of weighing to the nearest 1 mg, with a readability of 0.1 mg), Centrifuge (capable to produce a radial acceleration of around 80g to 90g at the outer end of the flasks or tubes), Distillation or evaporation apparatus, Drying oven (electrically heated, with ventilation port(s) fully open, capable of being maintained at a temperature of 102 °C ± 2 °C throughout its working space. The oven shall be fitted with a suitable thermometer.), Water bath (capable of being maintained at a temperature of 37,5 °C ± 2,5 °C, 50 °C ± 5 °C, 65 °C ± 5 °C and at boiling point), Fat-extraction flasks: ○ Mojonnier-type fat-extraction flasks ○ Extraction tubes-type fat extraction flask ○ Stoppers Rack, Wash bottle, Fat-collecting vessels, Measuring cylinders or delivering systems, Pipettes or delivering systems, Tongs, Blender, Boiling aids
5.	Total ash Cl. 4.8, Table 1, Sl.No.(iv)	Flat Bottom Dish, Muffle Furnace, Desiccator, Analytical Balance, Air-Oven, Burner
6.	Acid insoluble ash in dilute hydrochloric acid Cl. 4.8, Table 1, Sl. No.(v)	Flat-Bottom Dish of stainless-steel porcelain Silica or platinum, Muffle Furnace, Desiccator, Measuring Cylinder, Heating Mantle, Watch-glass, Water bath, Hot Air oven, Weighing Balance. Dil. HCl, Whatman Filter Paper No.42

7.	Solubility index Cl. 4.8, Table 1, Sl.No.(vi)	Thermometer, Water bath, Electronic Balance, Centrifuge, Electric Mixer, Mixing Jar, Interval Time
8.	Vitamin A (as retinol equivalent) Cl. 4.8, Table 1, Sl. No.(vii)	Methyl-t-butyl ether, n-Hexane, Ethanol Methanol, Iso-octane (2,2,4-trimethylpentane), Papain (from Carica papaya), Hydroquinone, Glacial acetic acid, Anhydrous sodium acetate, Dilute hydrochloric acid solution, HPLC mobile phase A, HPLC mobile phase B, Retinyl palmitate reference standard, Retinyl acetate reference standard, α -tocopheryl acetate reference standard, α -tocopherol reference standard, Retinyl palmitate stock standard solution, Retinyl acetate stock standard solution, α -tocopheryl acetate stock standard solution, α -tocopherol stock standard solution, HPLC system, HPLC column, Water bath, Centrifuge, UV-VIS spectrometer, Analytical balance, Amber HPLC vials, Disposable centrifuge tubes, Laboratory mechanical test tube shaker, Sonicator bath, One-mark volumetric flasks, Vacuum filtration apparatus, Laboratory glass bottles
9.	Vitamin D (expressed as chole-calciferol) Cl 4.8, Table 1, Sl.No. (viii)	Vitamin D2(ergocalciferol), Vitamin D3 (cholecalciferol), d6-Vitamin D2, d6-Vitamin D3, PTAD (4-phenyl-1,2,4-triazoline-3,5-dione), Formic acid, Potassium hydroxide, Pyrogallol, Ethanol, Methanol, Isooctane, Acetone, Acetonitrile, Ultra high performance liquid chromatography (UHPLC) system, consisting of dual pump system, a sample injector unit, a degasser unit, and a column oven, Triple quadrupole mass spectrometer, Solid core silica column, Spectrophotometer, Centrifuge tubes(polypropylene), Boiling tubes(glass), Water bath (range= 20 °C to 70 °C), Disposable syringes, Syringe filters, Centrifuges, Pasteur pipette(glass), Horizontal shaker, Micro centrifuge tubes, Filter membranes(0.45 μ m), Cryogenic vials
10.	Vitamin E(as α -tocopherol) Cl 4.8, Table 1, Sl. No. (ix)	Methyl-t-butyl ether, n-Hexane, Ethanol Methanol, Iso-octane (2,2,4-trimethylpentane), Papain (from Carica papaya), Hydroquinone, Glacial acetic acid, Anhydrous sodium acetate, Dilute hydrochloric acid solution, HPLC mobile phase A, HPLC mobile phase B, Retinyl palmitate reference standard, Retinyl acetate reference standard, α -tocopheryl acetate reference standard, α -tocopherol reference standard, Retinyl palmitate stock standard solution, Retinyl acetate stock standard solution, α -tocopheryl acetate stock standard solution, α -tocopherol stock standard solution, HPLC system, HPLC column, Water bath, Centrifuge, UV-VIS spectrometer, Analytical balance, Amber HPLC vials, Disposable centrifuge tubes, Laboratory mechanical test tube shaker, Sonicator bath, One-mark volumetric flasks, Vacuum filtration apparatus, Laboratory glass bottles
11.	Vitamin K Cl 4.8, Table 1, Sl. No. (x)	Acetic acid(glacial), Helium or nitrogen, Hexane(HPLC grade), Isooctane (2,2,4-trimethylpentane)(HPLC grade), Isopropanol (isopropyl alcohol)(HPLC grade), Methanol(HPLC grade),Phytonadione/ phyloquinone (vitamin K1), primary reference standard, distilled water, Ethanol, Sodium acetate(anhydrous), Zinc, Zinc chloride, HPLC system, Analytical balance(LC= 0.000 01

		g), Beakers, Centrifuge, Centrifuge tubes and caps, Gas regulator, compatible with helium or nitrogen, Gas sparge, tubing and filtering assembly, Magnetic stirrer and stir bar, centrifuge tubes, Pipet, Spectrophotometer, Volumetric flasks, Volumetric pipets, Vortex mixers.
12.	Thiamine Cl 4.8, Table 1, Sl. No. (xi)	Niacinamide (nicotinamide), Niacin (nicotinic acid), Pyridoxine hydrochloride, Riboflavin, Thiamine hydrochloride, Pyridoxamine dihydrochloride, Pyridoxal hydrochloride, 2 H ₄ -Niacinamide, 2 H ₄ -Nicotinic acid, 13 C ₄ -Pyridoxine: pyridoxine:HCl (4,5-bis(hydroxymethyl)- 13 C ₄), 2 H ₃ -Pyridoxal, 2 H ₃ -Pyridoxamine, 13 C ₄ -Thiamine chloride, 13 C ₄ , 15 N 2-Riboflavin, Acid phosphatase, Papain from Carica papaya, α -amylase from aspergillus oryzae, Hydrochloric acid concentrated, Ammonium formate, Glacial acetic acid, Formic acid, Laboratory water, Methanol, Ethylenediaminetetracetic acid, disodium salt dihydrate (EDTA), Potassium phosphate dibasic, meta-Phosphoric acid, Buffer solutions for pH meter calibration, Phosphoric acid, Potassium hydroxide, Waters Acquity BEH C18 column ²) or equivalent, UHPLC system, Waters Acquity Classic ²), or equivalent, Tandem quadrupole mass spectrometer with ESI probe, Waters Xevo TQS ²), or equivalent, Analytical balances, Water purifier, Water bath shaker, Bottle-top dispenser, pH meter, Vortex mixer, Multi-position magnetic stir plate, Room light shields, Graduated cylinders, Beakers, Volumetric flasks, Mobile phase bottles, Disposable plastic Pasteur pipettes, Amber bottles, Weighing vessels, Positive displacement pipettes, Positive displacement pipette tips, Plastic syringe, Syringe filters, Plastic centrifuge tubes, Autosampler vials, PTFE coated magnetic stir bars.
13.	Riboflavin Cl 4.8, Table 1, Sl. No. (xii)	Niacinamide (nicotinamide), Niacin (nicotinic acid), Pyridoxine hydrochloride, Riboflavin, Thiamine hydrochloride, Pyridoxamine dihydrochloride, Pyridoxal hydrochloride, 2 H ₄ -Niacinamide, 2 H ₄ -Nicotinic acid, 13 C ₄ -Pyridoxine: pyridoxine:HCl (4,5-bis(hydroxymethyl)- 13 C ₄), 2 H ₃ -Pyridoxal, 2 H ₃ -Pyridoxamine, 13 C ₄ -Thiamine chloride, 13 C ₄ , 15 N 2-Riboflavin, Acid phosphatase, Papain from Carica papaya, α -amylase from aspergillus oryzae, Hydrochloric acid concentrated, Ammonium formate, Glacial acetic acid, Formic acid, Laboratory water, Methanol, Ethylenediaminetetracetic acid, disodium salt dihydrate (EDTA), Potassium phosphate dibasic, meta-Phosphoric acid, Buffer solutions for pH meter calibration, Phosphoric acid, Potassium hydroxide, Waters Acquity BEH C18 column ²) or equivalent, UHPLC system, Waters Acquity Classic ²), or equivalent, Tandem quadrupole mass spectrometer with ESI probe, Waters Xevo TQS ²), or equivalent, Analytical balances, Water purifier, Water bath shaker, Bottle-top dispenser, pH meter, Vortex mixer, Multi-position magnetic stir plate, Room light shields, Graduated cylinders, Beakers, Volumetric flasks, Mobile phase bottles, Disposable plastic Pasteur pipettes, Amber bottles, Weighing vessels, Positive displacement pipettes, Positive displacement pipette tips, Plastic syringe, Syringe filters, Plastic

		centrifuge tubes, Autosampler vials, PTFE coated magnetic stir bars
14.	Niacin equivalent 4.8, Table 1, Sl.No. (xiii)	Niacinamide (nicotinamide), Niacin (nicotinic acid), Pyridoxine hydrochloride, Riboflavin, Thiamine hydrochloride, Pyridoxamine dihydrochloride, Pyridoxal hydrochloride, 2 H ₄ -Niacinamide, 2 H ₄ -Nicotinic acid, 13 C ₄ -Pyridoxine: pyridoxine:HCl (4,5-bis(hydroxymethyl)- 13 C ₄), 2 H ₃ -Pyridoxal, 2 H ₃ -Pyridoxamine, 13 C ₄ -Thiamine chloride, 13 C ₄ ,15 N 2-Riboflavin, Acid phosphatase, Papain from Carica papaya, α-amylase from aspergillus oryzae, Hydrochloric acid concentrated, Ammonium formate, Glacial acetic acid, Formic acid, Laboratory water, Methanol, Ethylenediaminetetracetic acid, disodium salt dihydrate (EDTA), Potassium phosphate dibasic, meta-Phosphoric acid, Buffer solutions for pH meter calibration, Phosphoric acid, Potassium hydroxide, Waters Acquity BEH C18 column2) or equivalent, UHPLC system, Waters Acquity Classic2), or equivalent, Tandem quadrupole mass spectrometer with ESI probe, Waters Xevo TQS2), or equivalent, Analytical balances, Water purifier, Water bath shaker, Bottle-top dispenser, pH meter, Vortex mixer, Multi-position magnetic stir plate, Room light shields, Graduated cylinders, Beakers, Volumetric flasks, Mobile phase bottles, Disposable plastic Pasteur pipettes, Amber bottles, Weighing vessels, Positive displacement pipettes, Positive displacement pipette tips, Plastic syringe, Syringe filters, Plastic centrifuge tubes, Autosampler vials, PTFE coated magnetic stir bars
15.	Pantothenic acid Cl 4.8, Table 1, Sl.No.(xiv)	Calcium d-pantothenate, Calcium pantothenate- [13 C ₆ , 15 N ₂], αAmylase, Acetonitrile, Ammonium acetate, Acetic acid, Formic acid, 1 % Formic acid in water, Balances, pH-meter, Homogenizer, Stir plate with magnetic stirrers, Filters, UHPLC-MS/MS system
16.	Vitamin B ₆ (pyridoxine) Cl 4.8, Table 1, Sl.No.(xv)	Niacinamide (nicotinamide), Niacin (nicotinic acid), Pyridoxine hydrochloride, Riboflavin, Thiamine hydrochloride, Pyridoxamine dihydrochloride, Pyridoxal hydrochloride, 2 H ₄ -Niacinamide, 2 H ₄ -Nicotinic acid, 13 C ₄ -Pyridoxine: pyridoxine:HCl (4,5-bis(hydroxymethyl)- 13 C ₄), 2 H ₃ -Pyridoxal, 2 H ₃ -Pyridoxamine, 13 C ₄ -Thiamine chloride, 13 C ₄ ,15 N 2-Riboflavin, Acid phosphatase, Papain from Carica papaya, α-amylase from aspergillus oryzae, Hydrochloric acid concentrated, Ammonium formate, Glacial acetic acid, Formic acid, Laboratory water, Methanol, Ethylenediaminetetracetic acid, disodium salt dihydrate (EDTA), Potassium phosphate dibasic, meta-Phosphoric acid, Buffer solutions for pH meter calibration, Phosphoric acid, Potassium hydroxide, Waters Acquity BEH C18 column2) or equivalent, UHPLC system, Waters Acquity Classic2), or equivalent, Tandem quadrupole mass spectrometer with ESI probe, Waters Xevo TQS2), or equivalent,

		Analytical balances, Water purifier, Water bath shaker, Bottle-top dispenser, pH meter, Vortex mixer, Multi-position magnetic stir plate, Room light shields, Graduated cylinders, Beakers, Volumetric flasks, Mobile phase bottles, Disposable plastic Pasteur pipettes, Amber bottles, Weighing vessels, Positive displacement pipettes, Positive displacement pipette tips, Plastic syringe, Syringe filters, Plastic centrifuge tubes, Autosampler vials, PTFE coated magnetic stir bars
17.	Dietary Folate Equivalent (DFE) Cl 4.8, Table 1, Sl. No. (xvi)	<u>UHPLC-MS/MS method as per AOAC 2013.13</u> UHPLC Column, liquid chromatograph, Detector, Amber glassware, Analytical balance, Homogeniser, pH meter, Water Bath, Whatman filter paper, Solid-phase extraction cartridges, Amber vials, L-ascorbic acid, Ammonium acetate, Disodium hydrogen phosphate powder, α -Amylase from porcine pancreas, α -Amylase from <i>Bacillus subtilis</i> , Protease from <i>Streptomyces griseus</i> , Ethanol, Methanol, Isopropanol, Acetonitrile, Formic acid, Acetic acid glacial, Sodium hydroxide solution, Hydrochloric acid, Ortho-phosphoric acid
18.	Biotin Cl. 4.8, Table 1, Sl. No. (xvii)	Laboratory reagent grade water, Sodium dihydrogen phosphate dihydrate, Disodium hydrogen phosphate dihydrate, Sodium hydroxide, Methanol, HPLC grade, Acetonitrile, HPLC grade, Ortho-phosphoric acid, PBS, Biotin, Biocytin, Sodium hydroxide, Sodium phosphate buffer, Phosphoric acid, HPLC system, Glass microfibre filters, Immunoaffinity column pack, SPE manifold, Autoclave, Centrifuge, Analytical balance, Amber glass screw-cap bottle, Horizontal shaker, Volumetric flasks, Pipettors, Measuring cylinder, Reaction vial, Heating block, Ultrasonic bath, Centrifuge tubes, Vortex mixer, Syringe filter, Disposable syringes, HPLC vials, HPLC System
19.	Vitamin B ₁₂ Cl. 4.8, Table 1, Sl. No.(xviii)	<u>Determination by Reversed Phase High Performance Liquid Chromatography (RP-HPLC) as per IS 16640:2018</u> Reagents Glacial acetic acid, Acetonitrile(HPLC grade), Drierite (anhydrous calcium sulfate), Ethanol, Formic acid, Potassium cyanide, Riboflavin, Sodium acetate anhydrous or sodium acetate trihydrate, TakaDiastase, Triethylamine(HPLC grade), Vitamin B12 (cyanocobalamin) primary reference standard Apparatus HPLC system, Oven(capable of maintaining temperatures of 95 °C ± 5 °C and 105 °C ± 5 °C), pH-meter, Analytical balance(LC= 0.00001 g), Beakers, glass, Bottle top dispenser, Cylinders, Desiccator, Filter paper, Whatman 2V ²) or equivalent OR <u>Ultra-High-Performance Liquid Chromatography method as per AOAC 2014.02</u> Balances, Sonicator, Oven, water bath, Rotary shaker, Heating block with nitrogen evaporation, Vortex, Homogenizer, Erlenmeyer flask,

		Whatman filter paper 602 ½ or 597 ½, Amber vials, Chromatographic system, Methanol, Acetonitrile, Acetic acid glacial, Sodium cyanide puriss, TFA for spectroscopy, Sodium acetate tri hydrate, Vitamin B ₁₂ (cyanocobalamin), Sodium hypochloride, α-Amylase from Bacillus subtilis
20.	Vitamin C Cl. 4.8, Table 1, Sl. No.(xix)	<u>2.6 -Dichlorophenol Indophenol Method as per IS 5838</u> Trichloroacetic Acid, Metaphosphoric Acid, Standard Ascorbic Acid Solution, Standard Indophenol Solution, Analytical Balance, Glass Stoppered Graduated Flask, Dessicator, Sodium Bicarbonate, Fluted Filter Paper, Amber Glass Stoppered Bottle, Refrigerator, Erlenmeyer Flasks, Titration Assembly, Mortar, Acid Washed Sand <u>2.4-Dinitrophenylhydrazine Method as per IS 5838</u> Photoelectric Colorimeter, Standard Ascorbic Acid Solution, Sulphuric Acid Solution, 2,4 Dinitrophenylhydrazine, Thiourea, Trichloroacetic Acid, Acid Washed Animal Charcoal, Sulphuric Acid, Mortar, Acid Washed Sand, Homogenizing Tube and Rod, Whatman No.42 Filter Paper, General Glasswares, Incubator, Titration Assembly <u>Determination of Vitamin C by (Ultra) High Performance Liquid Chromatography with Ultraviolet Detection ((U) HPLC-UV) as per IS 17176</u> Acetonitrile, Ascorbic acid, Decylamine, Phosphoric acid, Ultra-pure water, Sodium acetate trihydrate, Trichloroacetic acid (TCA), Tris [2-carboxyethyl]phosphine (TCEP), Isoascorbic acid, Orotic acid, Balances, Volumetric flasks, Beaker, pH meter, Paper filter, Membrane filters, UHPLC column, HPLC column, LC system, HPLC or UHPLC system
21.	Choline Cl. 4.8, Table 1, Sl. No.(xx)	Water, purified, MS grade or equivalent purity, Acetonitrile, Ammonium formate, Formic acid, Nitric acid, Isopropanol, Desiccant, L-carnitine, inner salt, Choline bitartrate, L-carnitine-d3 HCL, Choline-1,1,2,2-d 4 chloride, HPLC system, MS/MS system, Mass spectrometry software, Analytical column, Microwave, Microwave turntable Vortex mixer, Analytical balance, Horizontal shaker, Magnetic stir plate, Positive displacement pipets, Repeater positive displacement pipet, Polypropylene tubes, Digestion vessels for microwave digestion, graduated polypropylene tube, Glass containers, Syringe filters, Disposable syringes, Graduated cylinders, Magnetic stir bars, Autosampler vials and caps, Microcentrifuge tubes, Bottle top dispenser, Desiccator
22.	Iron Cl. 4.8, Table 1, Sl. No.(xxi)	<u>Inductively coupled plasma atomic emission spectrometry (ICPAES) method as per ISO 15151:2018</u> Water, Nitric acid (HNO₃), Nitric acid solution (HNO₃), Element stock solutions of Ca, P, K, Standard working solution of Fe, Internal standard solution H₂O₂, Analytical balance, One-mark volumetric

		flasks, One-mark pipettes, Micropipettes, Dispenser, High-density polyethylene bottles, Pressurized microwave assisted wet digestion system, ICP-AES instrument, Water bath, Appropriate grinding device, Sampler tubes, Cyclonic spray chamber, Concentric nebulize <u>Inductively coupled plasma mass spectrometry (ICP-MS) method as per ISO 21424</u> Methanol, Nitric acid (HNO₃) concentrated ultrapure reagent grade, Nitric acid (HNO₃), trace metal grade H₂O₂, Laboratory water, Surfactant, Argon gas, Helium gas, Hydrogen gas, Iron Standard Stock Solution, Standard Reference Material (SRM) of cereal with certified values of Fe, inductively coupled plasma mass spectrometer, Microwave oven, Hydrogen generator, Magnetic stir plate and PTFE coated magnetic stir bars, Analytical balance, Fume hood, Common laboratory glassware/plasticware, Repipetter, Bottle top dispenser, Volumetric pipettes, Digital pipettes <u>Method as per AOAC 985.35</u> Glassware, Evaporating dish, Atomic absorption spectrophotometer, Furnace, Water, Standard stock solution of Fe, Nitric acid, Lanthanum oxide, Lanthanum chloride solution, Cesium chloride solution, Filter pulp, Microwave Oven, Analytical Balance, Hot Plate, Steam Bath
23.	Sodium Cl. 4.8, Table 1, Sl. No.(xxii)	<u>Atomic Absorption Spectrometric Method as per IS 12760:2012</u> <u>Reagents:-</u> Nitric acid (HNO₃), concentrated, with a mass fraction of 65 %, Nitric acid (HNO₃), Lanthanum trichloride solution, Calcium ion stock solution, Sodium ion stock solution, Potassium ion stock solution, Magnesium ion stock solution, Standard working solution, containing 100 mg/l calcium, 20 mg/l sodium, 20 mg/l potassium and 10 mg/l magnesium ions, Light petroleum (petroleum ether), Hydrogen peroxide (H₂O₂) <u>Equipment:-</u> Analytical balance, capable of weighing to the nearest 1 mg, with a readability of 0.1 mg One-mark volumetric flasks, of nominal capacities 20 ml, 50 ml, 100 ml, 250 ml and 1000 ml, complying with the requirements of ISO 1042 One-mark pipettes, of nominal capacities 1 ml, 2 ml, 5 ml and 10 ml, complying with the requirements of ISO 648 Micropipette, capable of adjusting to between 1 ml and 5 ml, with plastic pipette tips, Graduated measuring cylinder, of capacity 10 ml High-density polyethylene (PE-HD) bottles, Silica crucibles, of capacity between 25 ml and 50 ml, Programmable furnace oven, capable of attaining a minimum temperature of 550 °C ± 25 °C and of programming with a heating rate of 50 °C/h, Open focused microwave-assisted wet digestion

		system, Pressurized microwave-assisted wet digestion system, provided with temperature and pressure controllers and an air cooling device, equipped with appropriate vessels of capacity 50 ml, commercially available or equivalent, Decomposition vessels, made of stainless steel, with adapted PTFE inner vessels of capacity 23 l with screw caps (pressurized wet decomposition PTFE vessel), commercially available or equivalent, Oven, capable of attaining a temperature of 150 °C (for digestion bombs), Flame atomic absorption spectrometer, with an air– acetylene burner; equipped with hollow cathode lamps of single element type or combined type, Water baths, Centrifuge, capable of producing a radial acceleration of 2500g, with tubes of capacity at least 150 ml, Appropriate grinding device, Sieve, free of contaminated material, with nominal size of aperture 0.5 mm <u>Inductively coupled plasma atomic emission spectrometry (ICP-AES) method as per ISO 15151:2018</u> Water, Nitric acid (HNO₃), Nitric acid solution (HNO₃), Element stock solutions of Ca, P, K, Standard working solution of Fe, Internal standard solution H₂O₂, Analytical balance, One-mark volumetric flasks, One-mark pipettes, Micropipettes, Dispenser, High-density polyethylene bottles, Pressurized microwave assisted wet digestion system, ICP-AES instrument, Water bath, Appropriate grinding device, Sampler tubes, Cyclonic spray chamber, Concentric nebulizer <u>Inductively coupled plasma mass spectrometry (ICP-MS) method as per ISO 21424</u> Methanol, Nitric acid (HNO₃) concentrated ultrapure reagent grade, Nitric acid (HNO₃), trace metal grade H₂O₂, Laboratory water, Surfactant, Argon gas, Helium gas, Hydrogen gas, Iron Standard Stock Solution, Standard Reference Material (SRM) of cereal with certified values of Fe, inductively coupled plasma mass spectrometer, Microwave oven, Hydrogen generator, Magnetic stir plate and PTFEcoated magnetic stir bars, Analytical balance, Fume hood, Common laboratory glassware/plasticware, Repipetter, Bottle top dispenser, Volumetric pipettes, Digital pipette
24.	Potassium Cl. 4.8, Table 1, Sl. No.(xxiii)	<u>Atomic Absorption Spectrometric Method as per IS 12760:2012</u> <u>Reagents:-</u> Nitric acid (HNO₃), concentrated, with a mass fraction of 65 %, Nitric acid (HNO₃), Lanthanum trichloride solution, Calcium ion stock solution, Sodium ion stock solution, Potassium ion stock solution, Magnesium ion stock solution, Standard working solution, containing 100 mg/l calcium, 20 mg/l sodium, 20 mg/l potassium and 10 mg/l magnesium ions, Light petroleum (petroleum ether), Hydrogen peroxide (H₂O₂)

Equipment:-

Analytical balance, capable of weighing to the nearest 1 mg, with a readability of 0.1 mg One-mark volumetric flasks, of nominal capacities 20 ml, 50 ml, 100 ml, 250 ml and 1000 ml, complying with the requirements of ISO 1042 One-mark pipettes, of nominal capacities 1 ml, 2 ml, 5 ml and 10 ml, complying with the requirements of ISO 648 Micropipette, capable of adjusting to between 1 ml and 5 ml, with plastic pipette tips, Graduated measuring cylinder, of capacity 10 ml High-density polyethylene(PE-HD) bottles, Silica crucibles, of capacity between 25 ml and 50 ml, Programmable furnace oven, capable of attaining a minimum temperature of $550\text{ }^{\circ}\text{C} \pm 25\text{ }^{\circ}\text{C}$ and of programming with a heating rate of $50\text{ }^{\circ}\text{C/h}$, Open focused microwave-assisted wet digestion system, Pressurized microwave-assisted wet digestion system, provided with temperature and pressure controllers and an air cooling device, equipped with appropriate vessels of capacity 50 ml, commercially available or equivalent, Decomposition vessels, made of stainless steel, with adapted PTFE inner vessels of capacity 23 l with screw caps (pressurized wet decomposition PTFE vessel), commercially available or equivalent, Oven, capable of attaining a temperature of $150\text{ }^{\circ}\text{C}$ (for digestion bombs), Flame atomic absorption spectrometer, with an air– acetylene burner; equipped with hollow cathode lamps of single element type or combined type, Water baths, Centrifuge, capable of producing a radial acceleration of 2500g, with tubes of capacity at least 150 ml, Appropriate grinding device, Sieve, free of contaminated material, with nominal size of aperture 0.5 mm

Inductively coupled plasma atomic emission spectrometry (ICP-AES) method as per ISO 15151:2018

Water, Nitric acid (HNO_3), Nitric acid solution (HNO_3), Element stock solutions of Ca, P, K, Standard working solution of Fe, Internal standard solution H_2O_2 , Analytical balance, One-mark volumetric flasks, One-mark pipettes, Micropipettes, Dispenser, High-density polyethylene bottles, Pressurized microwave assisted wet digestion system, ICP-AES instrument, Water bath, Appropriate grinding device, Sampler tubes, Cyclonic spray chamber, Concentric nebulizer

Inductively coupled plasma mass spectrometry (ICP-MS) method as per ISO 21424

Methanol, Nitric acid (HNO_3) concentrated ultrapure reagent grade, Nitric acid (HNO_3), trace metal grade H_2O_2 , Laboratory water, Surfactant, Argon gas, Helium gas, Hydrogen gas, Iron Standard Stock Solution, Standard Reference Material (SRM) of cereal with certified values of Fe, inductively coupled plasma mass spectrometer, Microwave oven, Hydrogen generator, Magnetic stir plate and

		PTFEcoated magnetic stir bars, Analytical balance, Fume hood, Common laboratory glassware/plasticware, Repipetter, Bottle top dispenser, Volumetric pipettes, Digital pipette
25.	Chloride Cl. 4.8, Table 1, Sl. No.(xxiv)	<u>Atomic Absorption Spectrometric Method as per IS 12760:2012</u> <u>Reagents:-</u> Nitric acid (HNO₃), concentrated, with a mass fraction of 65 %,Nitric acid (HNO₃),Lanthanum trichloride solution, Calcium ion stock solution, Sodium ion stock solution, Potassium ion stock solution, Magnesium ion stock solution, Standard working solution, containing 100 mg/l calcium, 20 mg/l sodium, 20 mg/l potassium and 10 mg/l magnesium ions, Light petroleum (petroleum ether), Hydrogen peroxide (H₂O₂) <u>Equipment:-</u> Analytical balance, capable of weighing to the nearest 1 mg, with a readability of 0.1 mg One-mark volumetric flasks, of nominal capacities 20 ml, 50 ml, 100 ml, 250 ml and 1000 ml, complying with the requirements of ISO 1042 One-mark pipettes, of nominal capacities 1 ml, 2 ml, 5 ml and 10 ml, complying with the requirements of ISO 648 Micropipette, capable of adjusting to between 1 ml and 5 ml, with plastic pipette tips, Graduated measuring cylinder, of capacity 10 ml High-density polyethylene(PE-HD) bottles, Silica crucibles, of capacity between 25 ml and 50 ml, Programmable furnace oven, capable of attaining a minimum temperature of 550 °C ± 25 °C and of programming with a heating rate of 50 °C/h, Open focused microwave-assisted wet digestion system, Pressurized microwave-assisted wet digestion system, provided with temperature and pressure controllers and an air cooling device, equipped with appropriate vessels of capacity 50 ml, commercially available or equivalent, Decomposition vessels, made of stainless steel, with adapted PTFE inner vessels of capacity 23 l with screw caps (pressurized wet decomposition PTFE vessel), commercially available or equivalent, Oven, capable of attaining a temperature of 150 °C (for digestion bombs), Flame atomic absorption spectrometer, with an air– acetylene burner; equipped with hollow cathode lamps of single element type or combined type, Water baths, Centrifuge, capable of producing a radial acceleration of 2500g, with tubes of capacity at least 150 ml, Appropriate grinding device, Sieve, free of contaminated material, with nominal size of aperture 0.5 mm <u>Inductively coupled plasma atomic emission spectrometry (ICP-AES) method as per ISO 15151:2018</u> Water, Nitric acid (HNO₃), Nitric acid solution (HNO₃), Element stock solutions of Ca, P, K, Standard working solution of Fe, Internal standard solution H₂O₂, Analytical balance, One-mark volumetric

		flasks, One-mark pipettes, Micropipettes, Dispenser, High-density polyethylene bottles, Pressurized microwave assisted wet digestion system, ICP-AES instrument, Water bath, Appropriate grinding device, Sampler tubes, Cyclonic spray chamber, Concentric nebulizer <u>Inductively coupled plasma mass spectrometry (ICP-MS) method as per ISO 21424</u> Methanol, Nitric acid (HNO₃) concentrated ultrapure reagent grade, Nitric acid (HNO₃), trace metal grade H₂O₂, Laboratory water, Surfactant, Argon gas, Helium gas, Hydrogen gas, Iron Standard Stock Solution, Standard Reference Material (SRM) of cereal with certified values of Fe, inductively coupled plasma mass spectrometer, Microwave oven, Hydrogen generator, Magnetic stir plate and PTFE coated magnetic stir bars, Analytical balance, Fume hood, Common laboratory glassware/plasticware, Repipetter, Bottle top dispenser, Volumetric pipettes, Digital pipette
26.	Calcium Cl. 4.8, Table 1, Sl. No.(xxv)	<u>Atomic Absorption Spectrometric Method as per IS 12760:2012</u> <u>Reagents:-</u> Nitric acid (HNO₃), concentrated, with a mass fraction of 65 %, Nitric acid (HNO₃), Lanthanum trichloride solution, Calcium ion stock solution, Sodium ion stock solution, Potassium ion stock solution, Magnesium ion stock solution, Standard working solution, containing 100 mg/l calcium, 20 mg/l sodium, 20 mg/l potassium and 10 mg/l magnesium ions, Light petroleum (petroleum ether), Hydrogen peroxide (H₂O₂) <u>Equipment:-</u> Analytical balance, capable of weighing to the nearest 1 mg, with a readability of 0.1 mg One-mark volumetric flasks, of nominal capacities 20 ml, 50 ml, 100 ml, 250 ml and 1000 ml, complying with the requirements of ISO 1042 One-mark pipettes, of nominal capacities 1 ml, 2 ml, 5 ml and 10 ml, complying with the requirements of ISO 648 Micropipette, capable of adjusting to between 1 ml and 5 ml, with plastic pipette tips, Graduated measuring cylinder, of capacity 10 ml High-density polyethylene (PE-HD) bottles, Silica crucibles, of capacity between 25 ml and 50 ml, Programmable furnace oven, capable of attaining a minimum temperature of 550 °C ± 25 °C and of programming with a heating rate of 50 °C/h, Open focused microwave-assisted wet digestion system, Pressurized microwave-assisted wet digestion system, provided with temperature and pressure controllers and an air cooling device, equipped with appropriate vessels of capacity 50 ml, commercially available or equivalent, Decomposition vessels, made of stainless steel, with adapted PTFE inner vessels of capacity 23 l with screw caps (pressurized wet decomposition PTFE vessel), commercially available or equivalent, Oven, capable of attaining a

		temperature of 150 °C (for digestion bombs), Flame atomic absorption spectrometer, with an air– acetylene burner; equipped with hollow cathode lamps of single element type or combined type, Water baths, Centrifuge, capable of producing a radial acceleration of 2500g, with tubes of capacity at least 150 ml, Appropriate grinding device, Sieve, free of contaminated material, with nominal size of aperture 0.5 mm <u>Inductively coupled plasma atomic emission spectrometry (ICP-AES) method as per ISO 15151:2018</u> Water, Nitric acid (HNO₃), Nitric acid solution (HNO₃), Element stock solutions of Ca, P, K, Standard working solution of Fe, Internal standard solution H₂O₂, Analytical balance, One-mark volumetric flasks, One-mark pipettes, Micropipettes, Dispenser, High-density polyethylene bottles, Pressurized microwave assisted wet digestion system, ICP-AES instrument, Water bath, Appropriate grinding device, Sampler tubes, Cyclonic spray chamber, Concentric nebulizer <u>Inductively coupled plasma mass spectrometry (ICP-MS) method as per ISO 21424</u> Methanol, Nitric acid (HNO₃) concentrated ultrapure reagent grade, Nitric acid (HNO₃), trace metal grade H₂O₂, Laboratory water, Surfactant, Argon gas, Helium gas, Hydrogen gas, Iron Standard Stock Solution, Standard Reference Material (SRM) of cereal with certified values of Fe, inductively coupled plasma mass spectrometer, Microwave oven, Hydrogen generator, Magnetic stir plate and PTFEcoated magnetic stir bars, Analytical balance, Fume hood, Common laboratory glassware/plasticware, Repipetter, Bottle top dispenser, Volumetric pipettes, Digital pipette
27.	Phosphorus Cl. 4.8, Table 1, Sl. No.(xxvi)	<u>Atomic Absorption Spectrometric Method as per IS 12760:2012</u> <u>Reagents:-</u> Nitric acid (HNO₃), concentrated, with a mass fraction of 65 %,Nitric acid (HNO₃),Lanthanum trichloride solution, Calcium ion stock solution, Sodium ion stock solution, Potassium ion stock solution, Magnesium ion stock solution, Standard working solution, containing 100 mg/l calcium, 20 mg/l sodium, 20 mg/l potassium and 10 mg/l magnesium ions, Light petroleum (petroleum ether), Hydrogen peroxide (H₂O₂) <u>Equipment:-</u> Analytical balance, capable of weighing to the nearest 1 mg, with a readability of 0.1 mg One-mark volumetric flasks, of nominal capacities 20 ml, 50 ml, 100 ml, 250 ml and 1000 ml, complying with the requirements of ISO 1042 One-mark pipettes, of nominal capacities 1 ml, 2 ml, 5 ml and 10 ml, complying with the requirements of ISO 648 Micropipette, capable of adjusting to

		between 1 ml and 5 ml, with plastic pipette tips, Graduated measuring cylinder, of capacity 10 ml High-density polyethylene(PE-HD) bottles, Silica crucibles, of capacity between 25 ml and 50 ml, Programmable furnace oven, capable of attaining a minimum temperature of $550\text{ }^{\circ}\text{C} \pm 25\text{ }^{\circ}\text{C}$ and of programming with a heating rate of $50\text{ }^{\circ}\text{C/h}$, Open focused microwave-assisted wet digestion system, Pressurized microwave-assisted wet digestion system, provided with temperature and pressure controllers and an air cooling device, equipped with appropriate vessels of capacity 50 ml, commercially available or equivalent, Decomposition vessels, made of stainless steel, with adapted PTFE inner vessels of capacity 23 l with screw caps (pressurized wet decomposition PTFE vessel), commercially available or equivalent, Oven, capable of attaining a temperature of $150\text{ }^{\circ}\text{C}$ (for digestion bombs), Flame atomic absorption spectrometer, with an air– acetylene burner; equipped with hollow cathode lamps of single element type or combined type, Water baths, Centrifuge, capable of producing a radial acceleration of 2500g, with tubes of capacity at least 150 ml, Appropriate grinding device, Sieve, free of contaminated material, with nominal size of aperture 0.5 mm <u>Inductively coupled plasma atomic emission spectrometry (ICP-AES) method as per ISO 15151:2018</u> Water, Nitric acid (HNO₃), Nitric acid solution (HNO₃), Element stock solutions of Ca, P, K, Standard working solution of Fe, Internal standard solution H₂O₂, Analytical balance, One-mark volumetric flasks, One-mark pipettes, Micropipettes, Dispenser, High-density polyethylene bottles, Pressurized microwave assisted wet digestion system, ICP-AES instrument, Water bath, Appropriate grinding device, Sampler tubes, Cyclonic spray chamber, Concentric nebulizer <u>Inductively coupled plasma mass spectrometry (ICP-MS) method as per ISO 21424</u> Methanol, Nitric acid (HNO₃) concentrated ultrapure reagent grade, Nitric acid (HNO₃), trace metal grade H₂O₂, Laboratory water, Surfactant, Argon gas, Helium gas, Hydrogen gas, Iron Standard Stock Solution, Standard Reference Material (SRM) of cereal with certified values of Fe, inductively coupled plasma mass spectrometer, Microwave oven, Hydrogen generator, Magnetic stir plate and PTFEcoated magnetic stir bars, Analytical balance, Fume hood, Common laboratory glassware/plasticware, Repipetter, Bottle top dispenser, Volumetric pipettes, Digital pipette
28.	Magnesium Cl. 4.8, Table 1, Sl. No.(xxvii)	<u>Atomic Absorption Spectrometric Method as per IS 12760:2012</u> <u>Reagents: -</u> Nitric acid (HNO₃), concentrated, with a mass fraction of 65 %, Nitric acid (HNO₃), Lanthanum trichloride solution, Calcium ion

stock solution, Sodium ion stock solution, Potassium ion stock solution, Magnesium ion stock solution, Standard working solution, containing 100 mg/l calcium, 20 mg/l sodium, 20 mg/l potassium and 10 mg/l magnesium ions, Light petroleum (petroleum ether), Hydrogen peroxide (H₂O₂)

Equipment: -

Analytical balance, capable of weighing to the nearest 1 mg, with a readability of 0.1 mg One-mark volumetric flasks, of nominal capacities 20 ml, 50 ml, 100 ml, 250 ml and 1000 ml, complying with the requirements of ISO 1042 One-mark pipettes, of nominal capacities 1 ml, 2 ml, 5 ml and 10 ml, complying with the requirements of ISO 648 Micropipette, capable of adjusting to between 1 ml and 5 ml, with plastic pipette tips, Graduated measuring cylinder, of capacity 10 ml High-density polyethylene(PE-HD) bottles, Silica crucibles, of capacity between 25 ml and 50 ml, Programmable furnace oven, capable of attaining a minimum temperature of 550 °C ± 25 °C and of programming with a heating rate of 50 °C/h, Open focused microwave-assisted wet digestion system, Pressurized microwave-assisted wet digestion system, provided with temperature and pressure controllers and an air cooling device, equipped with appropriate vessels of capacity 50 ml, commercially available or equivalent, Decomposition vessels, made of stainless steel, with adapted PTFE inner vessels of capacity 23 l with screw caps (pressurized wet decomposition PTFE vessel), commercially available or equivalent, Oven, capable of attaining a temperature of 150 °C (for digestion bombs), Flame atomic absorption spectrometer, with an air– acetylene burner; equipped with hollow cathode lamps of single element type or combined type, Water baths, Centrifuge, capable of producing a radial acceleration of 2500g, with tubes of capacity at least 150 ml, Appropriate grinding device, Sieve, free of contaminated material, with nominal size of aperture 0.5 mm

Inductively coupled plasma atomic emission spectrometry (ICP-AES) method as per ISO 15151:2018

Water, Nitric acid (HNO₃), Nitric acid solution (HNO₃), Element stock solutions of Ca, P, K, Standard working solution of Fe, Internal standard solution H₂O₂, Analytical balance, One-mark volumetric flasks, One-mark pipettes, Micropipettes, Dispenser, High-density polyethylene bottles, Pressurized microwave assisted wet digestion system, ICP-AES instrument, Water bath, Appropriate grinding device, Sampler tubes, Cyclonic spray chamber, Concentric nebulizer

Inductively coupled plasma mass spectrometry (ICP-MS) method as per ISO 21424

		Methanol, Nitric acid (HNO ₃) concentrated ultrapure reagent grade, Nitric acid (HNO ₃), trace metal grade H ₂ O ₂ , Laboratory water, Surfactant, Argon gas, Helium gas, Hydrogen gas, Iron Standard Stock Solution, Standard Reference Material (SRM) of cereal with certified values of Fe, inductively coupled plasma mass spectrometer, Microwave oven, Hydrogen generator, Magnetic stir plate and PTFE coated magnetic stir bars, Analytical balance, Fume hood, Common laboratory glassware/plasticware, Repipetter, Bottle top dispenser, Volumetric pipettes, Digital pipette
29.	Iodine Cl. 4.8, Table 1, Sl. No.(xxviii)	KOH pellets, Ammonium hydroxide, Sodium thiosulfate, Surfactant, Concentrated nitric acid, Perchloric acid (HClO ₄), Purified water (18 MΩ/cm), Iodide standard solution, triethylamine (TEA), Praseodymium (Pr) standard solution, Polypropylene tubes, capacity 50 ml and 100 ml, Oven (105 °C ± 5 °C), Open-vessel microwave digestion unit (optional), Analytical balance (LC=0.0001 g), Top-loader balance (LC= 0.01 g), ICP-MS system, Autosampler for ICP-MS, Adjustable volumetric pipets, Re-pipet volumetric dispensers, Polypropylene or polytetrafluoroethylene (PTFE) bottles, Disposable plastic syringes, Syringe filters, Beakers, Pump tubing
30.	Copper Cl. 4.8, Table 1, Sl. No.(xxix)	<u>Method as per IS 1599</u> Kjeldahl flask, Atomic absorption spectrophotometer, hydride generation vessel accessory, potentiometric recorder, Nitric acid, Perchloric acid, Sulphuric acid, Hydrochloric acid, Metal free water, Sodium sulphate, Sodium borohydride pellets, Potassium chloride Standard zinc solution, Weighing Balance, General Glasswares, Burner/ Heating Element/ Hot Plate <u>Inductively coupled plasma atomic emission spectrometry (ICP-AES) method as per ISO 15151:2018</u> Water, Nitric acid (HNO₃), Nitric acid solution (HNO₃), Element stock solutions of Ca, P, K, Standard working solution of Zn, Cu, Internal standard solution H₂O₂, Analytical balance, One-mark volumetric flasks, One-mark pipettes, Micropipettes, Dispenser, High-density polyethylene bottles, Pressurized microwave assisted wet digestion system, ICP-AES instrument, Water baths, Appropriate grinding device, Sampler tubes, Cyclonic spray chamber, Concentric nebulizer <u>Inductively coupled plasma mass spectrometry (ICP-MS) method as per ISO 21424</u> Methanol, Nitric acid (HNO₃) concentrated ultrapure reagent grade, Nitric acid (HNO₃), trace metal grade H₂O₂, Laboratory water, Surfactant, Argon gas, Helium gas, Hydrogen gas, Iron Standard Stock Solution, Standard Reference Material (SRM) of cereal with certified values of Fe, inductively coupled plasma mass spectrometer, Microwave oven, Hydrogen generator, Magnetic stir plate and PTFE

		coated magnetic stir bars, Analytical balance, Fume hood, Common laboratory glassware/plasticware, Repipetter, Bottle top dispenser, Volumetric pipettes, Digital pipettes
31.	Zinc Cl. 4.8, Table 1, Sl. No.(xxx)	<u>Method as per IS 1699</u> Kjeldahl flask, Atomic absorption spectrophotometer, hydride generation vessel accessory, potentiometric recorder, Nitric acid, Perchloric acid, Sulphuric acid, Hydrochloric acid, Metal free water, Sodium sulphate, Sodium borohydride pellets, Potassium chloride Standard zinc solution, Weighing Balance, General Glasswares, Burner/ Heating Element/ Hot Plate <u>Inductively coupled plasma atomic emission spectrometry (ICPAES) method as per ISO 15151:2018</u> Water, Nitric acid (HNO₃), Nitric acid solution (HNO₃), Element stock solutions of Ca, P, K, Standard working solution of Zn, Cu, Internal standard solution H₂O₂, Analytical balance, One-mark volumetric flasks, One-mark pipettes, Micropipettes, Dispenser, High-density polyethylene bottles, Pressurized microwave assisted wet digestion system, ICP-AES instrument, Water baths, Appropriate grinding device, Sampler tubes, Cyclonic spray chamber, Concentric nebulizer <u>Inductively coupled plasma mass spectrometry (ICP-MS) method as per ISO 21424</u> Methanol, Nitric acid (HNO₃) concentrated ultrapure reagent grade, Nitric acid (HNO₃), trace metal grade H₂O₂, Laboratory water, Surfactant, Argon gas, Helium gas, Hydrogen gas, Iron Standard Stock Solution, Standard Reference Material (SRM) of cereal with certified values of Fe, inductively coupled plasma mass spectrometer, Microwave oven, Hydrogen generator, Magnetic stir plate and PTFEcoated magnetic stir bars, Analytical balance, Fume hood, Common laboratory glassware/plasticware, Repipetter, Bottle top dispenser, Volumetric pipettes, Digital pipettes
32.	Manganese Cl. 4.8, Table 1, Sl. No.(xxxi)	<u>Inductively coupled plasma atomic emission spectrometry (ICPAES) method as per ISO 15151:2018</u> Water, Nitric acid (HNO₃), Nitric acid solution (HNO₃), Element stock solutions of Ca, P, K, Standard working solution of Zn, Cu, Internal standard solution H₂O₂, Analytical balance, One-mark volumetric flasks, One-mark pipettes, Micropipettes, Dispenser, High-density polyethylene bottles, Pressurized microwave assisted wet digestion system, ICP-AES instrument, Water baths, Appropriate grinding device, Sampler tubes, Cyclonic spray chamber, Concentric nebulizer <u>Inductively coupled plasma mass spectrometry (ICP-MS) method as per ISO 21424</u>

		Methanol, Nitric acid (HNO ₃) concentrated ultrapure reagent grade, Nitric acid (HNO ₃), trace metal grade H ₂ O ₂ , Laboratory water, Surfactant, Argon gas, Helium gas, Hydrogen gas, Iron Standard Stock Solution, Standard Reference Material (SRM) of cereal with certified values of Fe, inductively coupled plasma mass spectrometer, Microwave oven, Hydrogen generator, Magnetic stir plate and PTFE coated magnetic stir bars, Analytical balance, Fume hood, Common laboratory glassware/plasticware, Repipetter, Bottle top dispenser, Volumetric pipettes, Digital pipettes
33.	Selenium Cl. 4.8, Table 1, Sl. No.(xxii)	<u>Method as per IS 15303</u> Atomic Absorption Spectrometer, Source Lamps, Graphite Furnace, Readout Sample Dispensers, Vent, Cooling Water Supply, Membrane Filter Apparatus, Metal-Free-Water, Hydrochloric Acid, Nitric Acid, Magnesium Nitrate, Nickel, Nitrate, Phosphoric Acid, Palladium Nitrate, Citric Acid, Stock Selenium Solution, Chelating Resin, General Glasswares, Hot Plate <u>Inductively coupled plasma atomic emission spectrometry (ICP-AES) method as per ISO 15151:2018</u> Water, Nitric acid (HNO₃), Nitric acid solution (HNO₃), Element stock solutions of Ca, P, K, Standard working solution of Se, Internal standard solution H₂O₂, Analytical balance, One-mark volumetric flasks, One-mark pipettes, Micropipettes, Dispenser, High-density polyethylene bottles, Pressurized microwave assisted wet digestion system, ICP-AES instrument, Water baths, Appropriate grinding device, Sampler tubes, Cyclonic spray chamber, Concentric nebulizer <u>Determination by Inductively coupled plasma mass spectrometry (ICP-MS) method as per ISO 20649</u> Purified water, Concentrated nitric acid (HNO₃), Hydrogen peroxide (H₂O₂), Methanol, Potassium solution, Standard Solutions and Reference Materials, Microwave oven, ICP-MS, Various plasticware and pipettes, Analytical balance
34.	Inositol Cl. 4.8, Table 1, Sl. No.(xxiii)	Acetic acid, glacial, Chloroform, Diethyl ether, Drierite, Helium, Hexane, Hydrochloric acid, Metaphosphoric acid, Methanol, Myoinositol, Sodium chloride, Sodium hydroxide, Analytical balance, Centrifuge, Desiccator, Nitrogen evaporator, Oven, pH-meter, Stir plate, Vacuum manifold, Vortex mixer, System HPLC Columns, Beakers, Centrifuge tubes, Syringe filters, Filter paper, Conical flasks, Volumetric flasks, Funnels, Pipettes, Solid-phase extraction (SPE) cartridge, Syringes
35.	Taurine Cl. 4.8, Table 1, Sl. No.(xxxiv)	<u>Liquid Chromatographic method as per AOAC 997.05</u> <u>Equipment:</u> Liquid Chromatograph, LC Column, Filters, Glassware, pH Meter, Vortex mixer <u>Reagents:</u> Purified water, Acetonitrile, Acetic Acid, Sodium acetate buffer, Sodium carbonate, Carrez 1 and 2 reagent, Dansyl chloride reagent, Methylamine hydrochloride, Taurine standard

36.	Aerobic Plate count Cl. 4.8, Table 2, Sl. No. (i)	Diluents, Agar Medium, Oven, Incubator, Water bath, pH-meter, Petri dishes, Total delivery graduated pipettes, Colony-counting equipment, Tubes, flasks or bottles
37.	Coliform count Cl. 4.8, Table 2, Sl. No. (ii)	Crystal violet neutral red bile lactose (VRBL) agar, Brilliant green lactose bile broth, Apparatus for dry sterilization (oven) or wet sterilization (autoclave), Incubator, Water bath, Colony-counting equipment, Tubes, flasks or bottles, Durham tubes, pH-meter, Loop of platinum-iridium or nickel-chromium
38.	<i>Staphylococcus aureus</i> (Coagulase positive) Cl. 4.8, Table 2, Sl. No. (iii)	Diluent, Baird-parker Agar Medium, Potassium Tellurite solution, Egg Yolk Emulsion, Sulfamethazine, Brain-heart infusion broth, Rabbit Plasma, Apparatus for dry sterilization (oven) or wet sterilization (autoclave), Incubator, Drying cabinet or incubator, Water bath, Test tubes, flasks or bottles with screw caps, Petri dishes, Straight wire, Pasteur pipette, Total-delivery graduated pipettes, Spreaders, pH meter
39.	Yeast and mould count Cl. 4.8, Table 2, Sl. No. (iv)	<u>HORIZONTAL METHOD FOR THE ENUMERATION OF YEASTS AND MOULDS as per IS 16069(Part 1) and IS 16069(Part 2)</u> Diluent (0.1 % (mass concentration) peptone water broth), Culture medium (Dichloran 18 % (mass concentration) glycerol agar (DG18)), Dichloran-rose bengal chloramphenicol agar (DRBC), Incubator (capable of operating at 25°C±1°C), Total delivery pipettes, Water bath (capable of operating at 44 °C to 47 °C), pH meter, Bottles, flasks and tubes, Petri dishes (sterile, in glass or plastic, with a diameter 90 mm to 100 mm), Microscope (magnification 250 to 1 000 times)), Spreaders (made of glass or plastic of diameter less than 2 mm and length 80 mm), Binocular magnifier
40.	<i>Salmonella sp.</i> Cl. 4.8, Table 2, Sl. No. (v)	Buffered peptone water, Rappaport-Vassiliadis medium with soya (RVS broth) or Modified Semi-solid Rappaport-Vassiliadis (MSRV) agar and Muller-Kauffmann tetrathionate-novobiocin broth (MKTT) broth, Xylose Lysine Deoxycholate agar (XLD agar), Apparatus for dry sterilization (oven) or wet sterilization (autoclave), Drying cabinet or oven, Incubator, Water bath, Refrigerator, Freezer Sterile loops, pH-meter, Sterile tubes, bottles, or flasks, Sterile Petri dishes
41.	<i>Listeria monocytogenes</i> Cl. 4.8, Table 2, Sl. No. (vi)	Acridavine and nalidixic acid, Fraser broth, Listeria Agar, Apparatus for dry sterilization (oven) or wet sterilization (autoclave), Drying cabinet, Incubators, Water bath, Sterile loops, pH meter, Graduated pipettes or automatic pipettes, Petri dishes, Microscope, Refrigerator
42.	<i>Bacillus cereus</i> Cl. 4.8, Table 2, Sl. No. (vii)	Dilution fluid, Agar medium, Polymyxin B solution, Egg yolk emulsion, Complete medium (MYP agar), Sheep blood agar, Defibrinated sheep blood, Apparatus for dry sterilization (oven) or wet sterilization (autoclave), Drying cabinet, Incubator, Water baths, pH-meter, Petri dishes, Graduated pipettes, Spreaders
43.	Sulphite reducing <i>clostridia</i> Cl. 4.8, Table 2, Sl. No. (viii)	Iron sulfite agar, Saline peptone diluents, Homogenization equipment, Water bath, Anaerobic jars, Incubator, Test tubes

44.	<i>E. coli</i> , Cl. 4.8, Table 2, Sl. No. (ix)	Diluent, Lauryl sulfate broth, EC broth, Peptone water (indole free), Indole reagent (Kovacs' reagent), Apparatus for dry sterilization (oven) or wet sterilization (autoclave), Incubator (capable of operating at 37 °C ± 1 °C and 44 °C ± 1 °C), Water bath (capable of being maintained at 44 °C ± 1 °C), Test tubes, of dimensions approximately 16 mm × 160 mm and 18 mm × 180 mm or 20 mm × 200 mm, Sampling loops, made of platinum/iridium or nickel/chromium, approximately 3 mm in diameter, or approximately 10 µl sterile disposable sampling loops, Durham tubes, Total-delivery pipettes, having nominal capacities of 1 ml and 10 ml, pH-meter
45.	Lead Cl. 4.11, Table 3, Sl. No. (i)	<u>Method as per IS 12074</u> Atomic Absorption Spectrophotometer, Pure Lead Metal, Concentrated Nitric Acid, Concentrated Hydrochloric Acid, Standard Lead Solution, Drying Oven, Filter Papers, General Glasswares <u>Inductively Coupled Plasma-Mass Spectrometry Method as per AOAC 2015.01</u> ICP-MS instrument, High-purity grade liquid argon 99.996%, Analytical Balance, Clean Room Gloves, Microwave Digestion System, Autosampler Vials and Cups, Spatulas, Nitric acid (HNO₃), Hydrogen peroxide (H₂O₂), Stock standard solution, Single-element standards, Second source standard, Multi Element Stock Standard Solution, Internal Standard Solution, Certified Reference Materials, Analytical Balance
46.	Arsenic Cl. 4.11, Table 3, Sl. No. (ii)	<u>Method as per IS 11124</u> Atomic Absorption Spectrophotometer, Vapour Generation Kit, Concentrated Hydrochloric Acid, Concentrated Nitric Acid, Concentrated Sulphuric Acid, Potassium Iodide, Sodium Borohydride, Standard Arsenic Solution, Quartz Tube, Burner, Inert Gas Supply, Reaction Vessel, Stopper Assembly, Stirrer, Laboratory Glasswares <u>Inductively Coupled Plasma-Mass Spectrometry Method as per AOAC 2015.01</u> ICP-MS instrument, High-purity grade liquid argon 99.996%, Analytical Balance, Clean Room Gloves, Microwave Digestion System, Autosampler Vials and Cups, Spatulas, Nitric acid (HNO₃), Hydrogen peroxide (H₂O₂), Stock standard solution, Single-element standards, Second source standard, Multi Element Stock Standard Solution, Certified Reference Materials, Analytical Balance
47.	Tin Cl. 4.11, Table 3, Sl. No. (iii)	Water, Hydrochloric acid, Tin stock solution, Tin standard working solution, Tin standard working solution in diluted (evaporated) milk, Matrix modifier solutions, Balance, Water bath, One-mark volumetric flasks, Dosing pipettes, Atomic absorption spectrometer
48.	Cadmium Cl. 4.11, Table 3, Sl. No. (iv)	<u>Method as per IS 1699</u> Kjeldahl flask, Atomic absorption spectrophotometer, hydride generation vessel accessory, potentiometric recorder, Nitric acid, Perchloric acid, Sulphuric acid, Hydrochloric acid, Metal free water, Sodium sulphate, Sodium borohydride pellets, Potassium chloride

		Standard zinc solution, Weighing Balance, General Glasswares, Burner/ Heating Element/ Hot Plate <u>Inductively Coupled Plasma-Mass Spectrometry Method as per AOAC 2015.01</u> ICP-MS instrument, High-purity grade liquid argon 99.996%, Analytical Balance, Clean Room Gloves, Microwave Digestion System, Autosampler Vials and Cups, Spatulas, Nitric acid (HNO₃), Hydrogen peroxide (H₂O₂), Stock standard solution, Single-element standards, Second source standard, Multi Element Stock Standard Solution, Certified Reference Materials, Analytical Balance
49.	Melamine Cl. 4.11, Table 3, Sl. No. (v)	<u>Simultaneous quantitative determination of melamine by liquid chromatography electrospray ionization tandem mass spectrometry</u> Water, Acetonitrile, Ammonium acetate, Melamine and its standard solutions, Conical tubes, Centrifuge, Volumetric pipettes, Automatic micropipette, Nylon syringe filter, Degassing system, Analytical balance, Sonification device, Vials, LC-MS/MS equipment, HPLC Column, One-mark volumetric flasks <u>Quantitative analysis melamine in milk-based infant formula and cow milk by liquid chromatography using linear ion-trap mass spectrometry</u> Water, Acetonitrile, Ammonium acetate, Formic acid, Melamine and its standard solutions, Centrifuge tubes, Centrifuge, HPLC Column, Plastic syringes, Syringe filters, HPLC Surveyor MS pump, Analytical balance, One-mark volumetric flasks
50.	Bisphenol A(BPA) Cl. 5.1.1	<u>Gas chromatographic-mass spectrometric determination of Bisphenol A by ISO 18857-2</u> Hydrochloric acid or sulfuric acid, Acetone, Internal standard solutions, 2,2,2-Trifluoro-N-methyl-N-(trimethylsilyl)acetamide, Solid-phase material, on styrene-divinylbenzene polymer basis, Sand, Nitrogen, Sodium thiosulfate pentahydrate, Narrow-neck flat bottomed glass bottles, Solid-phase extraction cartridges, Vacuum or pressure assembly, Quartz wool, Pear-shaped flask, Evaporation assembly, e.g. rotary evaporator with vacuum stabiliser and water bath, Vials, brown glass with PTFE-lined septa, Stainless steel cocks, with stainless steel cone. Gas chromatograph OR <u>Method as per EN 13130-1:2004</u> Cruciform specimen supports, Tubes, Glass rods and beads, food cells, thermostatically controlled ovens or incubators

ANNEX B
Scheme of Inspection and Testing

1. LABORATORY - A laboratory shall be maintained which shall be suitably equipped (as per the requirement given in column 2 of Table 1) and staffed, where different tests given in the specification shall be carried out in accordance with the methods given in the specification.

1.1 The manufacturer shall prepare and implement a calibration plan for the test equipments.

2. TEST RECORDS – The manufacturer shall maintain test records for the tests carried out to establish conformity.

3. PACKING AND MARKING- –The Standard Mark, as given in the Schedule of the licence, shall be marked on the containers of Infant Food - Follow- Up Formula, or printed on the label applied to it, as the case may be, provided always that the product in each container to which this mark is thus applied, conform to every requirements of the specification.

3.1 Packing – The material shall be packed in suitable form of packing as per provisions of Clause 5.1.1 of IS 15757:2022. However, the packaging material shall be free from Bisphenol A(BPA), when tested as per ISO 18857-2 :2009 or EN 13130-13

3.2 The product shall be packed in quantities as stipulated under Legal Metrology (Packaged Commodities) Rules, 2011 and in accordance with requirements under the Food Safety and Standards (Packaging) Regulations, 2018 as per provisions of Clause 5.1.2 of IS 15757:2022.

3.3 Marking – The containers of the product shall bear legibly and indelibly the information as mentioned under clause 5.2.1 of IS 15757: 2022 In addition, the following details shall be mentioned on each container:

a) BIS Licence No. CM/L _____

b) BIS website details i.e – “For details of BIS Certification please visit www.bis.gov.in”.

3.3.1 In case of flexible packs, the following information as per provisions of Clause 5.2.1.1 of IS 15757:2022 shall be printed on the container: “On opening, transfer the contents of the pack to a clear air tight container. After each use, replace the lid tightly and store in a cool dry place.”

4. CONTROL UNIT – For the purpose of this scheme, the entire quantity of Infant Food - Follow- Up Formula manufactured and filled continuously in a day shall constitute a control unit.

5. LEVELS OF CONTROL – The tests as indicated in column 1 of Table 1 and the levels of control submitted by the manufacturer in column 3 of Table 1, shall be carried out on the whole production of the factory which is covered by this plan and appropriate records maintained in accordance with paragraph 2.0 above.

5.1 All the production which conforms to the Indian Standards and covered by the licence should be marked with Standard Mark.

6. HYGIENIC CONDITIONS – The product shall be manufactured and packed under strict hygienic conditions as per provisions of IS 2491, cross-referred in clause 4.12 of IS 15757: 2022.

7. REJECTIONS –Disposal of non-conforming product shall be done in such a way so as to ensure that there is no violation of provisions of BIS Act, 2016.

TABLE 1 (Levels of Control)
(Para 5 of Scheme of Inspection and Testing)

(1)				(2)	(3)		
Test Details				Test equipment requirement R: required (or) S: Sub-contracting permitted	Levels of Control		
Cl.	Requirement	Test Method			No. of Sample	Frequency	Remarks
		Clause	Reference				
4.1	Description	----					
4.1	a) Shall be free from lumps and coarse particles; and shall be uniform in appearance. It shall also be free from dirt, and extraneous matter, preservatives, added colour and flavour and from any material, which are harmful to infant's health. The flavor of the product in dry condition or of reconstituted feed shall be fresh and sweet.	----	IS 15757	---	One	Every half an hour	See Note 3 below
	b) Free from rancid taste and musty odour	----	IS 10641	R	One	Every half an hour	See Note 3 below
4.2	Scorched particles	----	IS 13500	R	Two	Each control unit	See Note 4 below
4.9	Protein Efficiency Ratio (PER)	---	IS 7481	---	----	-----	To be kept under abeyance

4.8,Table 1,Sl.No.(i)	Moisture	---	IS 16072 (Routine purpose) & IS 11623 (Reference purpose)	R	Two	Each control unit	See Note 4 below
4.8, Table 1, Sl.No.(ii)	Total milk protein	--	IS 11917	R	Two	Every control unit	See Note 4 below
4.8, Table 1, Sl.No.(iii)	Total fat	---	IS 19396	R	Two	Each control unit	See Note 4 below
4.8,Table 1,Sl.No.(iv)	Total ash	Annex-C	IS 14433	R	Two	Each control unit	See Note 4 below
4.8,Table 1,Sl.No.(v)	Acid insoluble ash in dilute hydrochloric acid	Annex-D	IS 14433	R	Two	Each control unit	See Note 4 below
4.8,Table 1,Sl.No.(vi)	Solubility Index	---	IS 12759	R	Two	Each control unit	See Note 4 below
4.8,Table 1,Sl.No.(vii)	Vitamin A (as retinol equivalent)	--	IS 16639	S	One	Once in a month	See note 6 below
4.8, Table 1, Sl.No. (viii)	Vitamin D (expressed as chole-calciferol)	--	IS 17177	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below
4.8, Table 1, Sl. No. (ix)	Vitamin E(as α -tocopherol)	--	IS 16639	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below
4.8, Table 1, Sl. No. (x)	Vitamin K	--	IS/ISO 21446	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below

4.8, Table 1, Sl. No. (xi)	Thiamine	----	IS 17669	S	One	Once in 3 months or whenever there is	See note 7 below
						change in formulation of the product or change in raw material supplier	
4.8, Table 1, Sl. No. (xii)	Riboflavin	----	IS 17669	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below
4.8, Table 1, Sl.No. (xiii)	Niacin equivalent	----	IS 17669	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below
4.8, Table 1, Sl.No. (xiv)	Pantothenic acid	---	IS 16642	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below
4.8, Table 1, Sl.No. (xv)	Vitamin B ₆ (pyridoxine)	----	IS 17669	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below
4.8, Table 1, Sl. No. (xvi)	Dietary Folate Equivalent (DFE)	--	AOAC 2013.13	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below
4.8, Table 1, Sl.No. (xvii)	Biotin	--	IS 17670	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below
4.8, Table 1, Sl.No.(xviii)	Vitamin B ₁₂	---	IS 16640 or AOAC 2014.02	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below

4.8,Table 1, Sl.No.(xix)	Vitamin C	--	IS 5838 or IS 17176	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below
4.8,Table 1, Sl.No.(xx)	Choline	---	IS 17668	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below
4.8,Table 1, Sl.No.(xxi)	Iron	----	AOAC 985.35 or ISO 15151 or ISO 21424	S	One	Once in a month	See note 6 below
4.8,Table 1, Sl.No.(xxii)	Sodium	----	IS 12760 or ISO 15151 or ISO 21424	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below
4.8,Table 1, Sl.No.(xxiii)	Potassium	----	IS 12760 or ISO 15151 or ISO 21424	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below
4.8,Table 1, Sl.No.(xxiv)	Chloride	----	IS 11763 or AOAC 2016.03	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below
4.8,Table 1, Sl.No.(xxv)	Calcium	----	IS 12760 or ISO 15151 or ISO 21424	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below
4.8,Table 1, Sl.No.(xxvi)	Phosphorus	----	IS 12756 or ISO 15151 or ISO 21424	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below

4.8,Table 1, Sl.No.(xxvii)	Magnesium	----	IS 12760 or ISO 15151 or ISO 21424	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below
4.8,Table 1, Sl.No.(xxviii)	Iodine	----	IS 17379	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below
4.8,Table 1, Sl.No.(xxix)	Copper	15 of IS 1699	IS 1699 or ISO 15151 or ISO 21424	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below
4.8,Table 1, Sl.No.(xxx)	Zinc	15 of IS 1699	IS 1699 or ISO 15151 or ISO 21424	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below
4.8,Table 1, Sl.No.(xxxi)	Manganese	----	ISO 15151 or ISO 21424	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below
4.8,Table 1, Sl.No.(xxii)	Selenium	----	IS 15303 or ISO 15151 or ISO 20649	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below
4.8,Table 1, Sl.No.(xxiii)	Inositol	---	IS 16649	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below
4.8, Table 1, Sl.No.(xxxiv)	Taurine	---	AOAC 2018.06 or AOAC 997.05	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below

4.8, Table 1, Sl.No.(xxxv)	Essential amino acids	--	Any validated international method	S	One	Once in 3 months or whenever there is change in formulation of the product or change in raw material supplier	See note 7 below
4.8, Table 2, Sl. No. (i)	Aerobic Plate count	--	IS 5402 (Part-1)	R	One	Each Control Unit	See note 5 below
4.8, Table 2, Sl. No. (ii)	Coliform count	--	IS 5401 (Part-1)	R	One	Each Control Unit	See note 5 below
4.8, Table 2, Sl. No. (iii)	<i>Staphylococcus aureus</i> (Coagulase positive)	--	IS 5887(Part 8/ Sec 1 or 2)	S	One	Once in a month	See note 6 below
4.8, Table 2, Sl. No. (iv)	Yeast and mould count	--	IS 16609-1 (for liquid formula) or IS 16069-2 (for powdered formula)	R	One	Each control unit	See note 5 below
4.8, Table 2, Sl. No. (v)	<i>Salmonella sp.</i>	--	IS 5887 (Part 3/ Sec 1)	S	One	Once in a month	See note 6 below
4.8, Table 2, Sl. No. (vi)	<i>Listeria monocytogenes</i>	--	IS 14988 (Part 1)	S	One	Once in a month	See note 6 below
4.8, Table 2, Sl. No. (vii)	<i>Bacillus cereus</i>		IS 5887(Part-6)	S	One	Once in a month	See note 6 below
4.8, Table 2, Sl. No. (viii)	Sulphite reducing <i>clostridia</i>	---	IS 18349 (Part 1)	S	One	Once in a month	See note 6 below
4.8, Table 2, Sl. No. (ix)	<i>E. Coli</i>	--	IS 16424	S	One	Once in a month	See note 6 below
4.11, Table 3, Sl. No. (i)	Lead	--	IS 12074 or AOAC 2015.01	S	One	Once in a month	See note 6 below

4.11, Table 3, Sl. No. (ii)	Arsenic	---	IS 11124 or AOAC 2015.01	S	One	Once in a month	See note 6 below
4.11, Table 3, Sl. No. (iii)	Tin	---	IS 18843	S	One	Once in a month	See note 6 below
4.11, Table 3, Sl. No. (iv)	Cadmium	15 of IS 1699	IS 1699 or AOAC 2015.01	S	One	Once in a month	See note 6 below
4.11, Table 3, Sl. No. (v)	Melamine	---	IS 16195	S	One	Once in a month	See note 6 below
5.1.1	Bisphenol A(BPA)	--	ISO 18857-2: 2009 or EN 13130-13	S	One	Each consignment of raw material received	Manufacturer to obtain test report/ test certificate from raw material supplier

Note 1: Whether test equipment is required or sub-contracting is permitted in column 2 shall be decided by the Bureau and shall be mandatory. Sub-contracting is permitted to a laboratory recognized by the Bureau or Government laboratories empaneled by the Bureau.

Note 2: Levels of control given in column 3 are only recommendatory in nature. The manufacturer may define the control unit/batch/lot and submit his own levels of control in column 3 with proper justification for approval by BO Head.

Note-3: A sample shall be taken at the packing/repacking stage after every half an hour which shall be examined visually to be free from lumps and coarse particles; uniform in appearance. It shall also be free from dirt, and extraneous matter, preservatives, added colour and flavour and from any material, which are harmful to infant's health. The flavor of the product in dry condition or of reconstituted feed shall be fresh and sweet. The product shall be examined by organoleptic methods for freedom from rancid taste and musty odour. If the sample does not conform to the specification in any one or more of these requirements, the material manufactured during the half an hour prior to drawal of sample shall be rejected for its conformity to these requirements of the specification

Note 4: Two samples shall be drawn from every control unit-one during the first half of the packing period and other during the second half of the packing period. These samples shall be individually tested for Scorched particles, Moisture, Total Milk Protein, Total Fat, Total ash, Total ash, Acid Insoluble Ash in dilute hydrochloric acid and Solubility Index. If any one of these sample(s) fail to conform to any one or more of these requirements(s) as given in the specification, the entire control unit shall either be rejected or reprocessed for its conformity to these requirements.

Note-5: One sample from every control unit shall be tested for the requirements of Aerobic plate count, Coliform count and Yeast and Mould count as laid down in the Indian Standard. If any of these samples fail to conform to any one or more of these requirements as laid down in the Indian Standard, the entire control unit shall either be rejected or reprocessed for its conformity to these requirements

Note-6: A sample shall be tested every month for Vitamin A, Iron, *Staphylococcus aureus*, *Salmonella*, *Listeria monocytogenes*, *Bacillus cereus*, Sulphite reducing *Clostridia*, *E. Coli*, Lead, Arsenic, Tin, Cadmium, Melamine. In case of failure of the sample in any one or more of these parameter(s), the root cause of failure shall be investigated, Corrective actions/Preventive be taken and dispatch to be kept on hold. Thereafter, the samples from two consecutive control units shall be tested for the parameter(s) where failure has occurred and once the same has been found to be conforming, original frequency of testing be restored and dispatch resumed.

Note-7: One sample shall be tested in every 3 months or whenever there is change in formulation of the product or change in raw material supplier for the requirements of Vitamin D, Vitamin E, Vitamin K, Thiamine, Riboflavin, Niacin equivalent, Pantothenic Acid, Vitamin B6, Dietary Folate Equivalent-DFE, Biotin, Vitamin B12, Vitamin C, Choline, Sodium, Potassium, Chloride, Calcium, Phosphorus, Magnesium, Iodine, Copper, Zinc, Manganese, Selenium, Inositol, Taurine and Essential amino acids, Calcium, Phosphorous, Sodium, Potassium, Magnesium and Chloride, as laid down in the Indian Standard. If the sample fails in any of these requirements, the entire control unit shall either be rejected or reprocessed for its conformity to these requirements