



उत्पाद मैनुअल
प्लेन बेयरिंग्स - मोटी दीवार के बुश,
सादे एवं कोरदार, पूर्ण गोलाकार (जोड़ अथवा चीरा रहित)
आईएस 14478: 2026 के अनुसार

PRODUCT MANUAL
PLAIN BEARINGS — THICK-WALLED BUSHES,
PLAIN AND FLANGE TYPE, FULL ROUND (WITHOUT ANY JOINT OR SLIT)
According to IS 14478: 2026

यह उत्पाद नियमावली सभी क्षेत्रीय/शाखा कार्यालयों और लाइसेंसधारियों द्वारा विभिन्न उत्पादों के लिए भारतीय मानक ब्यूरो (अनुरूपता मूल्यांकन) विनियम, 2018 की योजना-1 के अंतर्गत प्रमाणन के संचालन में एकरूपता और पारदर्शिता सुनिश्चित करने के लिए संदर्भ सामग्री के रूप में उपयोग की जाएगी। बीआईएस प्रमाणन प्राप्त करने के इच्छुक भावी आवेदक भी इस दस्तावेज़ का उपयोग कर सकते हैं।

This Product Manual shall be used as reference material by all Regional/Branch Offices & licensees to ensure uniformity of practice and transparency in operation of certification under Scheme-I of Bureau of Indian Standards (Conformity Assessment) Regulations, 2018 for various products. The document may also be used by prospective applicants desirous of obtaining BIS certification.

1.	मानक संख्या / IS No.	:	IS 14478: 2026
	शीर्षक / Title	:	Plain Bearings - Thick-Walled Bushes, Plain and Flange Type, Full Round (Without any Joint or Slit)
	संशोधनों की संख्या No. of amendments	:	0
2.	नमूनाकरण दिशानिर्देश / Sampling Guidelines		
a)	कच्चा माल Raw material	:	Lining Material (Cl. 6, Annex B of IS 14478) Backing Material (Cl. 6, Annex C of IS 14478) Solid Bronze Bushes (Cl. 6, Annex D of IS 14478) <i>Note: This section indicates the requirements for raw material (if specified in the IS) for which compliance is to be established during Grant of Licence/Change in Scope of Licence/Factory Surveillance.</i>
b)	समूहीकरण दिशानिर्देश Grouping Guidelines	:	Please refer ANNEX – A
c)	नमूने का परिमाण Sample Quantity	:	50 nos.
d)	परीक्षण अनुरोध में घोषित किए जाने वाले पैरामीटर Parameters to be Declared in Test Request	:	Following shall be declared in addition to the parameters given under S. No. 6: • Outside diameter • Width <i>Note: Apart from the above, any other requirements/ parameters may also be declared as per the standard, as applicable.</i>
3.	परीक्षण उपकरण की सूची List of Test Equipment	:	Please refer ANNEX – B

4.	निरीक्षण एवं परीक्षण योजना Scheme of Inspection and Testing	:	Please refer ANNEX – C
5.	एक दिन में संभावित परीक्षण Possible tests in a day	:	• All Tests <i>Note: This section is for the guidance of BIS Certification Officers/ Technical Auditors of BIS Authorized Outside Surveillance Agencies (OSAs) during factory inspection to provide ready reference regarding the tests which can be witnessed during the inspection in the factory by the officer/ auditor.</i>
6.	लाइसेंस का दायरा / Scope of the Licence:		
“License is granted to use Standard Mark as per IS 14478 : 2026 with the following scope:			
Name of the product		Plain Bearings - Thick-Walled Bushes, Plain and Flange Type, Full Round (Without any Joint or Slit)	
Type		• Cylindrical Non-Ferrous Bush • Flanged Non-Ferrous Bush • Cylindrical Bi-Metallic Bush • Flanged Bi-Metallic Bush • Flanged Tri-Metallic Bush	
Inside diameter		From ____mm to up to and including ____mm	
Material	Lining Material	(to be declared by the manufacturer)	
	Backing Material	(to be declared by the manufacturer)	
	Solid Bronze Bushes	(to be declared by the manufacturer)	

BUREAU OF INDIAN STANDARDS
MANAK BHAVAN, 9, BAHADUR SHAH ZAFAR MARG, NEW DELHI-110002
www.bis.gov.in

ANNEX -A **Grouping Guidelines**

1. Plain Bearings - Thick-Walled Bushes, Plain and Flange Type, Full Round (Without any Joint or Slit) as per IS 14478: 2026 may be classified as below:

Type		• Cylindrical Non-Ferrous Bush • Flanged Non-Ferrous Bush • Cylindrical Bi-Metallic Bush • Flanged Bi-Metallic Bush • Flanged Tri-Metallic Bush
Inside diameter		From ____ mm to up to and including ____ mm
Material	Lining Material	(to be declared by the manufacturer)
	Backing Material	(to be declared by the manufacturer)
	Solid Bronze Bushes	(to be declared by the manufacturer)

2. Based on the above classification, following grouping guidelines shall be followed for considering Grant of Licence (GoL)/Change in Scope of Licence (CSoL):
 - Samples of each type of Thick-Walled Bushes shall be tested separately. However, if flanged type is tested, corresponding cylindrical type may also be covered in the scope of licence. For instance, if flanged non-ferrous bush is tested, cylindrical non-ferrous bush may also be covered.
 - Samples of a particular type of Thick-Walled Bushes with the lowest inside diameter and the highest inside diameter, of any outside diameter and of any width shall be tested to cover the entire range of inside diameters for that particular type for which the firm intends to obtain licence.
 - Samples of Thick-Walled Bushes for each type of material (for Lining Material, Backing Material and Solid Bronze Bushes) shall be tested separately.
3. The Firm shall declare all the varieties of Thick-Walled Bushes intended to be covered in the Licence. The Scope of Licence may be restricted based on the Manufacturing and testing capabilities of the Manufacturer.
4. During the operation of the Licence, BO shall ensure that all the varieties covered in the Licence are tested in rotation, to the extent possible.

ANNEX- B
List of Test Equipments
(Indicative List, For Guidance Only)

Sl. No.	Cl. Ref.	Tests used in with Clause Reference	Test Equipment
1	4 Table 1 & Table 2	Dimensions	Vernier Caliper Micrometer
2	5	Tolerances	Dial Gauge Height Gauge Angle Protractor
3	6 Annex B, Annex C & Annex D	Material	Spectrometer Sample preparation tools
4	8	Surface Roughness	Surface Roughness Tester

The above list is indicative only and may not be treated as exhaustive.

ANNEX C

Scheme of Inspection and Testing

1. QUALITY ASSURANCE PLAN

1.1 It is expected that during operation of BIS licence manufacturers will implement a Quality Assurance Plan (QAP) i.e. a plan of regular testing and in-process controls, designed to ensure that the product bearing the Standard Mark conforms to all requirements of the Indian Standard.

1.2 The manufacturers shall define a Quality Assurance Plan (QAP) defining the control unit (i.e. lot/batch etc.), the levels of control (i.e. the frequency and number of samples for conducting the different tests as per the Indian Standard) and declare the arrangement for testing i.e. whether in-house or sub-contracting/ sharing for each applicable test and submit the same to BIS Branch Office for information. The manufacturer shall comply with the QAP and maintain test records in accordance with para 2.1.

1.3 Recommended Levels of Control/ Control Unit:

1.3.1 For the guidance of manufacturers, the recommended definition of control unit is: *entire quantity of Thick-Walled Bushes of same type, same inside diameter, same outside diameter and same width, manufactured in a day under similar process condition from the same consignment of raw materials* shall constitute a control unit.

1.3.2 For the guidance of manufacturers in preparing the Quality Assurance Plan, recommended levels of control are given in [Table 1](#). Manufacturer has the discretion of declaring their own levels of control or accept the levels of control given in this document.

1.3.3 The manufacturer shall ensure inspection and testing as per the Quality Assurance Plan submitted by them on the whole production of the factory which is covered by this plan.

1.4 However, all manufacturers shall ensure compliance of their products to all the requirements of the Indian Standard.

2. ENSURING COMPLIANCE THROUGH TESTING

The manufacturers shall ensure compliance of their products to all the requirements of the Indian Standard for which they may have in-house test facilities. However, there is no obligation to maintain in-house laboratory. Licensee may use alternative arrangements for tests of the production as per the declared QAP. Various alternatives are available for operation of BIS certification as given below and the relevant guidelines for availing such relaxations by the manufacturers, as amended from time to time, are to be referred:

- i) Shared testing resources like common facility,
- ii) Cluster based testing facility,
- iii) Sub-contracting to outside laboratories which may either be:
 - a) BIS recognised/ empanelled laboratories, or
 - b) Any accredited laboratory as per ISO/IEC 17025

2.1 Test Records- The manufacturers shall maintain test records for the tests carried out (either in-house or at a sub-contracted or at shared test facility) to establish conformity of the product to the Standard for operation of licence. For the tests being subcontracted or conducted at a shared test facility, test results issued by the laboratories or test facilities, shall be made available for inspection by BIS.

3. PACKING AND MARKING

The Standard Mark as given in the Schedule of the licence shall be incorporated legibly and indelibly on the packaging of the Thick-Walled Bushes provided always that the Thick-Walled Bushes so marked conforms to each requirement of the specification.

3.1 Marking of Thick-Walled Bushes shall be done as per Cl. 10 of IS 14478:2026.

3.2 **Additional Marking requirements:** The Thick-Walled Bushes shall also be marked with the following additional requirement on its packaging:

a) "For BIS certification details please visit www.bis.gov.in"

4. REJECTION

The production which conforms to the Indian Standard and covered under the scope of this licence shall be marked with the Standard Mark. Disposal of non-conforming product shall be done in such a way so as to ensure that there is no violation of provisions of BIS Act, 2016.

TABLE-1
(Recommended Levels of Control by BIS- for Guidance Only)

(1)				(2)		
Test Details				Levels of Control		
Cl.	Requirement	Test Methods		No. of Sample	Frequency	Remarks
		Clause	Reference			
6	Material	ANNEX B ANNEX C ANNEX D	IS 14478	Each Consignment		No further testing is required if accompanied with the Test Certificate or ISI marked.
4	Dimensions	Table 1 Table 2	IS 14478	05	Each Control Unit	Firm to also have adequate in-process controls to check compliance of this parameter as per the tolerances given in the Indian Standard. Appropriate records shall be maintained by the manufacturer for evidence of conformity.
5	Tolerances		IS 919 (Part 1) IS 919 (Part 2)	05	Each Control Unit	
8	Surface Roughness		IS 3073	01	Each Control Unit	